

UTILITY COMMITTEE

Meeting Notice

Governing Body: Utility Committee of Boone, Iowa

Date of Meeting: October 20, 2025

Time of Meeting: 5:00 P.M.

Place of Meeting: City Hall Council Chambers

The City will have this meeting available via Zoom. To join the meeting via internet and/or phone please use the link and/or phone number below. If your computer does not have a mic and you wish to speak, you will have to call in.

https://us06web.zoom.us/j/85655797097?pwd=C3bDBI14bFyUDtTHOUBJZ0ahBVBSq6.1

Meeting ID: 856 5579 7097

Passcode: 243693

Phone: 1-301-715-8592 or 1-253-215-8782

- 1. Call Meeting to Order.
- 2. Approve Minutes from the August 18, 2025, Meeting.
- 3. Discuss Water System Modeling and Water Projects. SEH.
- 4. Review the August and September 2025 US Water Monthly Report.
- 5. Meter Upgrade Report.
 - a. August
 - b. September
- 6. Stop Box Repair/Shut Off Report.
 - a. August
 - b. September
- 7. Other Business.
- 8. Adjourn.



UTILITY COMMITTEE

Meeting Notice

Governing Body: Utility Committee of Boone, Iowa

Date of Meeting: August 18, 2025

Time of Meeting: 4:00 P.M.

Place of Meeting: City Hall Council Chambers

The City will have this meeting available via Zoom. To join the meeting via internet and/or phone please use the link and/or phone number below. If your computer does not have a mic and you wish to speak, you will have to call in.

https://us06web.zoom.us/j/85218247136?pwd=zeFY61ZVGRMbXJze8NP36al2WpS9qS.1

Meeting ID: 852 1824 7136

Passcode: 014044

Phone: 1-301-715-8592 or 1-253-215-8782

1. Call Meeting to Order.

Present: Angstrom, Moorman

Absent: Byrd

Others present: Andrews, Gjersvik, Elmquist, Montag, Majors, JD Roberts, Katie Kinsey,

McKenzie Hunt, Rolling Meadows Representatives

2. Approve Minutes from the July 21, 2025 Meeting.

Moorman moved; Angstrom seconded to approve the minutes from July 21, 2025 meeting. Ayes: all those in attendance. Nays: none.

3. Discuss High Water Bill. – Rolling Meadows Association.

The Rolling Meadows Association met with the Utility Committee to discuss a water leak that occurred at the end of May 2025. Andrews advised that the total water consumption due to the leak and subsequent flushing was 239,550 cubic feet, totaling \$17,684.92. Andrews provided a timeline of his communications with Rolling Meadows regarding the SCADA system and acknowledged the technical issues with the communication system between the City of Boone water meter and the Rolling Meadows SCADA system, which resulted in a failure to notify or trigger an alarm for the water leak. Andrews also presented the Committee with several payment options for Rolling Meadows Association:

- 1. Continue with billing Rolling Meadows Water District for the total amount of \$17,684.92.
- 2. Bill Rolling Meadows Water District for the cost of production of the lost water, totaling \$5,879.18.
- 3. Bill Rolling Meadows Water District for the approximate 250,000 gallons of water flushed after the repairs, and for staff time to flush and test, at their agreed rate, for a total of \$1,810.90.

4. Forgive the total bill to Rolling Meadows Water District in the amount of \$17,684.92.

Moorman moved; Angstrom seconded, to approve Option 2: to bill Rolling Meadows Water District for the cost of production of the lost water in the amount of \$5,879.18. Ayes: all those in attendance. Nays: none.

4. Discuss Allowing the City of Ogden to Temporarily Deliver Digester Sludge to the Boone Wastewater Plant.

Roberts explained that the City of Ogden reached out to him regarding the possibility of the Wastewater Plant accepting some of their digester sludge during the months of January 2026 and July 2026, not to exceed 60,000 gallons per month. The City of Ogden agrees to pay the City of Boone \$0.175 for each gallon delivered. Elmquist advised that staff would have the City of Ogden review and approve the one (1) year agreement before bringing it to the full Council for review. Moorman moved; Angstrom seconded, to recommend approval of the agreement to the full Council, allowing the City of Ogden to deliver digester sludge to the Wastewater Plant. Ayes: all those in attendance. Nays: none.

5. Update on Status of Water Projects.

McKenzie Hunt, and Katie Kinsey, Short Elliott Hendrickson (SEH), presented a power point presentation on the status of the Water System Improvements:

Water Supply Improvements – Well Additions: Due to permitting and pumping restrictions on the Jordan Aquifer, the City will no longer pursue two Jordan wells and will instead develop two (2) alluvial wells. The cost for one (1) alluvial well is estimated at \$650,000.00, with an additional \$300,000.00 needed to extend electrical service. This alternative is projected to save approximately \$1.88 million compared to the original plan. Design for the first well will be completed by October 2025, with site evaluation for the second ongoing.

Water Treatment Plant Improvements — The pilot study has been revised in response to reliance on high-nitrate wells. Phase 1 will assess potential operational adjustments to the existing WTP, and Phase 2 will test ion exchange technology for nitrate removal. The study begins in September. Iowa regulations require action if nitrate levels exceed 7 mg/L; thus, the treatment goal is 6 mg/L. Approximately 60% of system flow will need treatment by 2044. Space constraints at the Water Treatment Plant are being reviewed to accommodate the ion exchange system.

High Service Pump Station (HSPS) Improvements – Four (4) new 250 HP pumps with VFDs will be installed to enhance system capacity. Minimal electrical work is expected, but the aging generator will be replaced due to insufficient capacity. Valve and sodium hypochlorite system upgrades are included to ensure reliability and compliance. A new flow meter and actuated valve will be added to enable bypass automation around the lime softening units—essential for operations when Daisy Brands comes online in 2028.

Ground Storage Reservoir Rehabilitation – Design is complete, and the team is awaiting the Iowa Department of Natural Resources (IDNR) Construction Permit. Funding of \$500,000.00

has been approved through CDBG, with release expected in September. The project will be bid once funds are available.

Distribution System Improvements – Hydraulic modeling is underway to evaluate system impacts once the Daisy Brands facility becomes operational, with water demand expected to reach 2.0 MGD at 60 psi between 2028 and 2032. Without improvements, the system will face reduced capacity at the Industrial and Clinton Towers, high pressure on the west side of town, and insufficient pressure at the Daisy site.

Three (3) solutions were evaluated and presented:

Solution 1. Involves upsizing existing water mains (\$4.5M) but does not resolve tower capacity or meet pressure targets.

Solution 2. Proposes installing altitude valves (cost not estimated), but results in unacceptably high west-side pressures.

Solution 3. The preferred option, create a new pressure zone by building a booster station, installing a check valve, upsizing a water main along Scenic Valley Railway, and redirecting flow via valve closure. This option costs \$2.5M and has no identified limitations.

Daisy Water Tower – The tower project is on hold pending completion of hydraulic modeling and selection of a preferred distribution solution. Final design will consider FAA airspace clearance, ground elevation, the required 60 psi pressure at the Daisy site, and modeling results to ensure efficiency and performance.

Kinsey also discussed CIP planning regarding a water tower on the west side of town.

6. Update on Status of Wastewater Improvement Projects. *Gjersvik presented the status of the Wastewater Improvements Projects:*

Headworks Improvements Project – The project was rebid and received five (5) bids, all under the engineer's estimate. The City Council awarded the project to Shank Contractors at the second Council meeting in July. A preconstruction meeting will be scheduled soon to initiate project coordination.

Digester Replacement Project – Design is underway to replace two (2) aging digesters with a new single bolted-steel tank digester. This project may be eligible for CDBG funding, pending completion of the Water Ground Storage Reservoir (GSR) Tank Project.

Wastewater System Expansion Project – Design of all improvements is currently underway. A 30% design review meeting was held with the SEH team in July to discuss routing and final sizing of the pump station and force main. A site visit was also conducted in July with SEH and the US Water operations team in Story City to evaluate the proposed sludge fan press equipment. All teams were impressed with the equipment's suitability for use in Boone. The City is currently working with Daisy Brands and their wastewater engineers to determine discharge permit limits,

which will guide final sizing of the improvements. A meeting with the IDNR Pretreatment Coordinator is scheduled this week to further discuss permit limits for Daisy.

7. Update on Hancock Drive Extension.

Gjersvik advised that this project is currently out for bids, with the bid opening scheduled for September 9, 2025, at 2:00 p.m. Contract award is anticipated in the fall, with the potential to begin installation of underground utilities and grading later this year, weather permitting.

8. Review the July 2025 US Water Monthly Report.

The Committee reviewed the July 2025 US Water Monthly Report.

- 9. Meter Upgrade Report.
 - a. July

Staff installed sixteen (16) meters in July, five (5) of those being new service meters.

- 10. Stop Box Repair/Shut Off Report.
 - a. July

Staff reported that twenty-four (24) accounts qualified to be on the shut-off list. There are one hundred seventy (170) stop boxes that need repaired, with seventy-three (73) of those having lead service lines.

- 11. Other Business.
- 12. Adjourn.

With no further business coming before the Committee the meeting adjourned at 5:35 p.m.



Water Treatment Plant Expansion

Boone, IA

BOONE 182275 | October 15, 2025



Building a Better World for All of Us®

Engineers | Architects | Planners | Scientists



October 15, 2025

RE: Water Treatment Plant Expansion Hydraulic Modeling Results Boone, IA SEH No. BOONE 182275

Perry Gjersvik, PE City of Boone, IA 923 8th Street Boone, IA 50036

Dear Mr. Gjersvik:

This report provides results from the hydraulic model developed for the water distribution system in the City of Boone, Iowa. It has been prepared in support of the City's planning efforts as it prepares to accommodate the development of the Daisy Brand Industry facility.

The modeling effort evaluates multiple alternatives to ensure the distribution system can reliably meet future demands associated with the new industrial development, while still maintaining the same level of service to the remainder of the community. The analysis includes assessments of system capacity, pressure zones, and potential infrastructure improvements to support long-term growth and operational resilience.

We appreciate the opportunity to support the City of Boone in this important phase of infrastructure planning and look forward to continued collaboration as the project progresses.

Katrina L. Kinsey, PE Project Manager (Lic. IA, KS, MN, MO, NE, SD, VA, WI)

x:\ae\b\boone\182275\5-final-dsgn\53-dsgn-info\hydraulic modeling\hydraulic modeling results - report.docx

Hydraulic Modeling Results

Water Treatment Plant Expansion Boone, IA

SEH No. BOONE 182275

October 15, 2025



I hereby certify that this engineering document was prepared by me or under my direct personal supervision and that I am a duly licensed Professional Engineer under the laws of the State of Iowa.

October 15, 2025

Date

Katrina L. Kinsey, P.E. Iowa Reg. No. P21084 My license renewal date is December 31, 2025 Pages covered by this seal:

ΑII

Short Elliott Hendrickson Inc. 5414 NW 88th Street Suite 140 Johnston, IA 50131



Executive Summary

Daisy Brand Industry (Daisy) is planning to construct a new facility on the east side of Boone, Iowa. To ensure the City of Boone's municipal water distribution system can support Daisy's projected water demands without compromising service reliability, a comprehensive hydraulic modeling study was conducted. This study evaluated existing system performance, identified infrastructure limitations, and proposed phased improvements to accommodate Daisy's full buildout by 2032.

The modeling revealed that Daisy's location and high water usage introduce significant challenges to the distribution system, including reduced pressures near the Daisy site, elevated pressures on the west side, increased velocities along Hancock Drive, and imbalanced tower floating between the Clinton Street and Industrial Towers. These impacts are especially pronounced under maximum day demand conditions and necessitate targeted infrastructure upgrades.

Several alternatives were evaluated, including water main replacements, transmission main loops, and pressure zone modifications. The recommended solution is a phased approach that balances immediate operational needs with long-term system reliability and expansion.

Phase 1, targeted for completion by August 2028, includes construction of a 12-inch water main along the Boone & Scenic Valley Railroad, installation of a booster station at the proposed Daisy Tower, a check valve on Eastgate Drive, abandonment of the Greene Street Tower, and reconnection of the water main near Coal Road and W 12th Street. These improvements will establish a dedicated pressure zone for Daisy, achieving the required pressure and improving system performance at a cost of approximately \$2.8 million.

Phase 2, to be implemented when funding becomes available, involves construction of the North Transmission Main and installation of an altitude valve at the Industrial Tower. This phase will provide system redundancy, support future growth, and enhance operational control. The estimated cost for Phase 2 is approximately \$8.6 million.

This phased strategy ensures that Daisy's integration into the Boone water distribution system is both technically feasible and financially manageable, while preserving service quality for existing customers and supporting future development.

Contents

Letter of Transmittal Certification Page Executive Summary Contents

1	Intro	oduction	1
	1.1	Existing Distribution System Performance	1
	1.2	Daisy Brands Industry	1
2	Infra	astructure Improvements Alternatives	4
	2.1	Water Main Upgrades	2
	2.2	Altitude Valves	6
	2.3	Water Main Improvements and Boosted Daisy Zone	6
3	Red	commendation	10
4	Pha	sing of Recommendations	12

i

List of Appendices

Appendix A Figures

Hydraulic Modeling Results

Water Treatment Plant Expansion

Prepared for City of Boone, IA

1 Introduction

Daisy Brand Industry (Daisy) is planning to construct a new facility within the City of Boone, Iowa (Boone). To ensure that the integration of this industry does not adversely affect the existing municipal water distribution system, a series of hydraulic modeling scenarios have been conducted. These evaluations identify the infrastructure upgrades necessary to support Daisy's water demands while maintaining reliable service throughout the community.

1.1 Existing Distribution System Performance

The City of Boone's water distribution system currently relies on a single water supply source located on the far northwest side of the system. In contrast, its largest water customer, Xenia Rural Water District (Xenia), is situated on the far east side. Before assessing the potential impacts of the proposed Daisy facility, it is essential to understand the performance of the existing system.

Table 1 summarizes key performance factors under average day demand (ADD) and maximum day demand (MDD) conditions. These metrics serve as a baseline for evaluating future infrastructure improvements in response to Daisy's integration.

Scenario	Clinton Street Tower & Industrial Tower Peak Floating Difference (ft)	Peak System Pressure – W 3 rd St & S Montana St (psi)	System Pressure - Daisy Brands Site (psi)	Hancock Dr Velocities (ft/s)
Existing ADD	3*	105	60.0 - 64.5	1.08
Existing MDD	5*	106	59.5 – 64.0	1.35

Table 1 – Existing Distribution System Performance

1.2 Daisy Brands Industry

Daisy plans to construct a new facility on the far east side of Boone, south of the Xenia connection. The hydraulic modeling effort focused on identifying infrastructure solutions that will support full buildout of Daisy's operations by the year 2032.

^{*}If Xenia doesn't draw water, then both towers float together

Daisy has requested a pressure range of 55–60 psi at their site. To meet this requirement, projected water demands were scaled over time to determine the necessary infrastructure upgrades for each phase of development. The timing of these improvements is directly tied to Daisy's projected water demand schedule, as shown in Table 2.

Table 2 – Daisy Brands Industry Water Demand Projections

Year	Average Day Demand (MGD)	Maximum Day Demand (MGD)
2028	0.8	0.8
2029	1.1	1.1
2030	1.4	1.4
2031	1.7	1.7
2032	2.0	2.0

In addition to annual increases, Daisy's water usage fluctuates significantly throughout the day. These fluctuations are captured in Table 3 and will be modeled using a diurnal curve to reflect the instantaneous and normal demand periods.

Table 3 – Daisy Brands Industry Demand Fluctuations for ADD and MDD

Year	Instantaneous Demand (MGD)	Instantaneous Demand Timeframe	Normal Demand (MGD)	Normal Demand Timeframe
Aug 2028	4,000	midnight – 1:30 am	349	1:30 am – midnight
Aug 2029	4,000	midnight – 1:30 am	587	1:30 am – midnight
Aug 2030	4,000	midnight – 2:00 am	730	2:00 am – midnight
Aug 2031	4,000	midnight – 3:00 am	778	3:00 am – midnight
Aug 2032	4,000	midnight – 3:00 am	1,016	3:00 am – midnight

The addition of another high-demand user on the far east side of the distribution system introduces significant hydraulic challenges. These include:

- Imbalanced tower floating between the Clinton Street and Industrial Towers
- Elevated pressures in the western portion of the system
- · Reduced pressures near the Daisy site
- Increased velocities along Hancock Drive

These impacts highlight the need for strategic infrastructure upgrades to maintain system reliability and performance as the Daisy facility comes online as shown in Table 4.

Table 4 – Existing Distribution System Performance with Daisy

Scenario	Clinton Street Tower & Industrial Tower Peak Floating Difference (ft)	Peak System Pressure – W 3 rd St & S Montana St (psi)	System Pressure – Daisy Brands Site (psi)	Hancock Dr Velocities (ft/s)
Existing ADD	18	132	Cannot Sustain (+) Pressure	13.24
Existing MDD	20	132	Cannot Sustain (+) Pressure	14.62

2 Infrastructure Improvements Alternatives

As various infrastructure improvement options are evaluated, certain components will be constructed regardless of the selected alternative. These shared improvements include the installation of a 1-million-gallon elevated storage tank, referred to as the Daisy Tower, located north of the Daisy site, and a 12-inch water main loop. This loop will extend from the existing dead-end water main on Eastgate Drive, pass through the Daisy site to the Daisy Tower, and continue along the newly constructed Hancock Drive to Corporal Roger Snedden Drive.

2.1 | Water Main Upgrades

The initial modeling strategy aimed to optimize the distribution system through passive infrastructure upgrades, minimizing the need for ongoing maintenance or operational oversight by the City. This phase focused on enhancing water mains within the system.

2.1.1 Water Main Improvements (3 Projects)

Three key water main replacement projects were evaluated to address tower, pressure, and velocity issues as shown in Figure A-1, with results summarized in Table 5 below, and a total estimated cost of \$4,600,000.

• Project 1: Hancock Drive Water Main

Upgrade the existing 8-inch water main to a 12-inch main to improve pressure at the Daisy site and reduce peak demand velocities along Hancock Drive. The estimated cost for this project is \$1,100,000.

Project 2: 8th and 9th Streets Water Main

Replace small-diameter mains with a 16-inch water main to mitigate peak pressure concerns near W 3rd Street and S Montana Street. The estimated cost for this project is \$1,500,000.

Project 3: Industrial Park Road Water Main

Replace the existing 8-inch diameter water main with a 16-inch water main to enable the Clinton Street Tower and Industrial Tower to float together, improving system balance. The estimated cost for this project is \$2,000,000.

Table 5 – Distribution System Performance after Construction of the 2.1.1 P	rojects
---	---------

Scenario	Clinton Street Tower & Industrial Tower Peak Floating Difference (ft)	Peak System Pressure – W 3 rd St & S Montana St (psi)	System Pressure – Daisy Brands Site (psi)	Hancock Dr Velocities (ft/s)
2044 ADD	2.5	115	Cannot Sustain (+) Pressure	7.61
2044 MDD	4.0	114	Cannot Sustain (+) Pressure	7.60

Limitation:

Although these upgrades were implemented, the system was not permitted to return to its previous performance level, and the pressure at the Daisy site remained insufficient to maintain

positive pressure. Additionally, the proposed Daisy Tower is unable to recover, rendering it ineffective for improving system performance. As a result of these limitations, further alternatives were evaluated.

2.1.2 Expanded Water Main Improvements – Including a Significant Transmission Main Project

Including all three projects from Alternative 2.1.1, an additional alternative was considered involving a substantial 16-inch transmission main loop to address the issue throughout the distribution system. The route of this additional alternative is shown in Figure A-1, with results summarized in Table 6 below, and an estimated cost of \$4,600,000 for Alternative 2.1.1 improvements and an estimated cost of \$7,800,000 for Alternative 2.1.2 improvements for a total estimated project cost of \$12,400,000.

Scenario	Clinton Street Tower & Industrial Tower Peak Floating Difference (ft)	Peak System Pressure – W 3 rd St & S Montana St (psi)	System Pressure – Daisy Brands Site (psi)	Hancock Dr Velocities (ft/s)
2044 ADD	negligible	107	45 – 56	3.34
2044 MDD	nealiaible	108	45 – 56	3.34

Table 6 – Distribution System Performance after Construction of the 2.1.2 Project

Limitation:

This alternative enabled the distribution system to nearly regain its previous performance levels. However, the associated costs of projects from Alternatives 2.1.1 and 2.1.2 appear disproportionately high. As a result, the modeling outcomes led to further investigation of alternative solutions.

2.1.3 North Transmission Main

Another alternative was evaluated to address the tower capacity, pressure, and velocity concerns resulting from the addition of Daisy. This option, illustrated in Figure A-2 and summarized in Table 7 below, has an estimated cost of \$8,500,000. It includes the construction 6.2 mile transmission main consisting of a 16-inch transmission main from the water treatment plant to Marion Street, continuing south to connect with the existing 16-inch water main at the intersection of Marion Street and W 10th Street. From the point where the 16-inch main bends south, a 12-inch transmission main will extend north to W 22nd Street, then east to Quartz Avenue, and finally south to tie into the dead-end 12-inch water main located north of the intersection of Quartz Avenue and Industrial Park Road.

Table 7 – Distribution System Performance after Construction of the 2.1.3 Project

Scenario	Clinton Street Tower & Industrial Tower Peak Floating Difference (ft)	Peak System Pressure – W 3 rd St & S Montana St (psi)	System Pressure – Daisy Brands Site (psi)	Hancock Dr Velocities (ft/s)
2044 ADD	negligible	110	Cannot Sustain (+) Pressure*	12.89
2044 MDD	negligible	105	Cannot Sustain (+) Pressure*	12.85

^{*} System pressure at Daisy Brands site remains insufficient to maintain positive pressure for 2044 ADD and 2044 MDD when the water main between the Daisy Tower and the Daisy site is changed to a 16-inch water main.

Limitation:

Despite the upgrades, the system was unable to maintain positive pressure at the Daisy site, and velocities within the Hancock Drive water main remain excessively high. Additionally, the proposed Daisy Tower was unable to recover, making it ineffective in improving overall system performance. Due to these limitations, additional alternatives were evaluated.

2.2 Altitude Valves

Preliminary hydraulic modeling was performed to assess the feasibility of installing altitude valves at both the Industrial Tower and Clinton Street Tower, as illustrated in Figure B, with the intent of redirecting flow toward the proposed Daisy Tower. However, this approach was quickly ruled out due to significant pressure spikes observed throughout the distribution system, particularly on the west side, where pressures exceeded 200 psi. These extreme conditions raised serious operational concerns.

Limitation:

This alternative was deemed impractical due to the excessive pressures generated across the system, which pose unacceptable risks to infrastructure and operations.

2.3 Water Main Improvements and Boosted Daisy Zone

To achieve the water demands required and the target pressure of 55–60 psi at the Daisy site, the recommended approach is to establish a dedicated pressure zone that includes both Daisy and the proposed Daisy Tower. This strategy also involves identifying and implementing necessary water main upgrades to enhance the overall efficiency of the distribution system.

A booster station will be installed at the proposed Daisy Tower to elevate the pressure to the desired 55-60 psi requested by Daisy. This installation will effectively create a separate pressure zone around the Daisy site, operating independently from the rest of the distribution network. To fully isolate this new zone, a check valve must be installed on the existing water main along Eastgate Drive.

To enhance the overall efficiency of the distribution system, alternative water main routes were evaluated.

2.3.1 Boone & Scenic Valley Railroad Water Main with Boosted Daisy Zone

One alternative that was considered to improve the distribution system was to install a 12-inch water main along the Boone & Scenic Valley Railroad. Modeling results indicate that this alternative is feasible with the addition of a boosted zone for Daisy. However, for optimal results, the connection point on Industrial Park Road should be located as close to the Industrial Tower as possible.

This setup causes the Industrial and Clinton Street Towers to float together, but it also significantly reduces the need of the Greene Street Tower due to the height of the tower and the existing altitude valve, causing the tower to never empty and remain full. As a result, there is potential for water age and stagnant water issues in the Greene Street Tower causing it to be obsolete. Ideally, in this scenario, the Greene Street Tower should be removed from service.

The last improvement needed to enhance the overall efficiency of the distribution system is to close a valve on a 12" water main located near Coal Road and W 12th Street and reconnect the water main in this area. Closing this valve will reduce the pressures on the west side of the distribution system by creating more headloss within the water mains.

The improvements described in this alternative are illustrated in Figure C, with modeling results summarized in Table 8. The estimated cost for these improvements, which include a booster station, check valve, abandonment of the Greene Street Tower, Boone & Scenic Valley Railroad water main, and the water main reconnection near Coal Road and W 12th Street, is approximately \$2,800,000.

Scenario	Clinton Street Tower & Industrial Tower Peak Floating Difference (ft)	Peak System Pressure – W 3 rd St & S Montana St (psi)	System Pressure – Daisy Brands Site (psi)	Hancock Dr Velocities (ft/s)
2044 ADD	negligible	115	47 – 65*	5.24
2044 MDD	negligible	121	47 – 65*	5.23

Table 8 – Distribution System Performance after Construction of the 2.3.1 Project

Limitation:

Although the Industrial and Clinton Street Towers float together and system pressure at the Daisy site, as well as velocities in the Hancock Drive water main, appear to be within acceptable operating ranges, pressure levels on the west side of the distribution system remain higher than desired.

2.3.2 North Transmission Main with Boosted Daisy Zone

Another alternative considered to improve the distribution system is the installation of a transmission main, as outlined in Section 2.1.3. Modeling results show that the North Transmission Main, combined with a boosted zone for the Daisy area, is a viable option compared to the Boone & Scenic Valley Railroad alignment. This transmission main offers a more direct connection to the Industrial Tower, which helps reduce headloss throughout the system.

^{*} System pressure at Daisy Brands site is 55–65 psi for 2044 ADD and 2044 MDD when the water main between the Daisy Tower and the Daisy site is changed to a 16-inch water main.

This setup causes the Industrial and Clinton Street Towers to float together, but it also significantly reduces the need of the Greene Street Tower due to the height of the tower and the existing altitude valve, causing the tower to only cycle 2 feet every day. As a result, there is potential for water age and stagnant water issues in the Greene Street Tower causing it to be obsolete. Ideally, in this scenario, the Greene Street Tower should be removed from service.

To further enhance the overall efficiency of the distribution system, an additional improvement involves closing a valve on a 12-inch water main near Coal Road and W 12th Street and reconnecting the water main in that area. This improvement increases headloss within the system, which helps lower pressures on the west side of the distribution system.

The improvements described in this alternative are illustrated in Figure D, with modeling results summarized in Table 9. The estimated cost for these improvements, which include a booster station, check valve, abandonment of the Greene Street Tower, North Transmission Main, and the reconnection near Coal Road and W 12th Street, is approximately \$9,300,000.

Although the North Transmission Main is a costly addition to the distribution system, it offers several benefits, as it provides operators with a redundant water main from the water treatment plant to the east side of town, increasing system reliability. This redundancy also supports future expansion by enabling the addition of new water users on the north and east sides of town.

Scenario	Clinton Street Tower & Industrial Tower Peak Floating Difference (ft)	Peak System Pressure – W 3 rd St & S Montana St (psi)	System Pressure – Daisy Brands Site (psi)	Hancock Dr Velocities (ft/s)
2044 ADD	negligible	105	51 – 65*	4.94
2044 MDD	negligible	108	51 – 65*	4.80

Table 9 – Distribution System Performance after Construction of the 2.3.2 Project

Limitation

While this alternative appears to be the ideal long-term solution, its high cost may require several years to secure funding.

2.3.3 Combined Water Main with Boosted Daisy Zone

A practical solution would be to proceed with Alternative 2.3.1, pursue funding, and subsequently implement the North Transmission Main (Alternative 2.1.3) at a later date. This long-term solution includes a booster station, check valve, abandonment of the Greene Street Tower, Boone & Scenic Valley Railroad water main, and the water main reconnection near Coal Road and W 12th Street to be completed in the near future and the North Transmission Main to be completed at a later date when funding can be secured.

With two transmission mains supplying the Industrial Tower, it becomes the lead tower and tends to float at a higher elevation than the Clinton Street Tower, which can result the Industrial Tower overflowing. To prevent this, installing a control valve at the Industrial Tower is recommended.

^{*} System pressure at Daisy Brands site is 57–65 psi for 2044 ADD and 2044 MDD when the water main between the Daisy Tower and the Daisy site is changed to a 16-inch water main.

In this configuration, elevated pressures on the west side of the distribution system during maximum day demand are primarily caused by the control valve, which is designed to prevent overflow of the Industrial Tower. Pressure spikes occur immediately after the valve closes and just before the third high service pump shuts down. To reduce these spikes, a failsafe mechanism should be considered that shuts down the third pump before the valve closes. Without this spike, pressures on the west side of the system remain close to current operating conditions. On typical days, the Industrial Tower does not overflow as frequently, which results in lower system pressures. The control valve at the Industrial Tower is only activated when two high service pumps are operating at the same time.

Modeling results for this alternative are summarized in Table 10. The estimated cost for implementing Alternative 2.3.1 is approximately \$2,800,000. The future cost for Alternative 2.1.3, along with the installation of an altitude valve at the Industrial Tower, is approximately \$8,600,000.

Table 10 – Distribution System Performance after Construction of the 2.3.3 Project

Scenario	Clinton Street Tower & Industrial Tower Peak Floating Difference (ft)	Peak System Pressure – W 3 rd St & S Montana St (psi)	System Pressure – Daisy Brands Site (psi)	Hancock Dr Velocities (ft/s)
2044 ADD	2.5	104	51 – 65**	4.88
2044 MDD	5.0	115*	51 – 65**	4.86

^{*} High pressure is caused by overflow at the Industrial Tower, occurring just as the control valve closes and before the third high service pump shuts down.

^{**} System pressure at Daisy Brands site is 57–65 psi for 2044 ADD and 2044 MDD when the water main between the Daisy Tower and the Daisy site is changed to a 16-inch water main.

3 Recommendation

To address the immediate hydraulic challenges of the distribution system when Daisy becomes operational in August 2028 while balancing long-term system reliability and cost-effectiveness, it is recommended to proceed with Alternative 2.3.3 as a phased infrastructure improvement strategy:

Phase 1: Immediate Construction

Construct the Boone & Scenic Valley Railroad water main with a dedicated booster station at the proposed Daisy Tower. This phase includes:

- Establishing a boosted pressure zone for the Daisy site.
- Installing a check valve on Eastgate Drive to isolate the boosted zone.
- Abandoning the Greene Street Tower, which becomes obsolete due to minimal cycling and potential water age issues.
- Reconnecting the water main near Coal Road and W 12th Street to reduce west-side pressures.
- Estimated cost: \$2,800,000.

Benefits:

- Achieves acceptable pressure and velocity levels at the Daisy site.
- Keeps Clinton Street and Industrial Towers floating together.
- Provides a cost-effective solution with manageable short-term investment.
- Eliminates the Greene Street Tower from the distribution system, thereby removing the
 problematic altitude valve. This also reduces dependence on the tower, helping to
 improve overall water quality.

Phase 2: Future Expansion

Construct the North Transmission Main when funding becomes available. This phase includes:

- A 6.2-mile transmission main from the water treatment plant to the north and east sides
 of town.
- Installation of an control valve at the Industrial Tower to prevent overflow and manage pressure spikes.
- Estimated cost: \$8,600,000.

Benefits:

- Adds redundancy and reliability to the distribution system.
- Supports future expansion and new water users.
- Reduces headloss and improves system efficiency.
- Enhances operational control and balances tower performance.

 Implement a failsafe mechanism to shut down the third high service pump before the altitude valve closes to mitigate pressure spikes. 				
•	Monitor and adjust control settings at Clinton Street and Industrial Towers to optimize usable volume and system pressures.			

Operational Considerations:

4 Phasing of Recommendations

To address current system performance limitations while planning for future expansion and reliability, a phased implementation strategy is proposed. This plan outlines two distinct phases, an immediate improvement phase to be completed by August 2028 before Daisy becomes operational, and a future expansion phase to be implemented when funding becomes available.

Phase 1: Immediate Implementation (Target Completion - 2028)

Phase 1 focuses on constructing the Boone & Scenic Valley Railroad water main and establishing a dedicated pressure zone for the Daisy site. This includes the installation of a booster station at the proposed Daisy Tower to achieve the target pressure. A check valve will be installed on Eastgate Drive to isolate the boosted zone from the rest of the distribution system.

As part of this phase, the Greene Street Tower will be removed from service due to its limited cycling and potential for water age issues. Additionally, the water main near Coal Road and W 12th Street will be reconnected to reduce pressures on the west side of the system. These improvements will enhance pressure and velocity performance along Hancock Drive and reduce reliance on aging infrastructure.

The estimated cost for Phase 1 is approximately \$2,800,000. Completion of this phase is targeted for August of 2028.


Phase 2: Future Expansion (Timeline Dependent on Funding Availability)

Phase 2 involves the construction of the North Transmission Main, which consists of approximately 6.2 miles of 16-inch and 12-inch water mains. This transmission main will provide a more direct connection from the water treatment plant to the north and east sides of town, improving system reliability and supporting future growth.

A control valve will be installed at the Industrial Tower to prevent overflow and manage pressure spikes. This valve will be activated only when two high service pumps are operating simultaneously. A failsafe mechanism is recommended to shut down the third pump prior to valve closure to mitigate pressure spikes.

The estimated cost for Phase 2, including the North Transmission Main and control valve installation, is approximately \$8,600,000. This phase will be implemented when adequate funding is secured.

Appendix A Figures




Project Number: BOONE 182275
Print Date: 8/18/2025

Map by: dbrissett
Projection:
Source:

BOONE WATER MODEL Boone, IA

FIGURE A-1

Water Main Improvements (3 Projects) and Expanded Water Main Improvements




Project Number: BOONE 182275
Print Date: 8/18/2025

Map by: dbrissett
Projection:
Source:

BOONE WATER MODEL Boone, IA


FIGURE A-2
North Transmission Main Improvement



Project Number: BOONE 182275
Print Date: 8/18/2025


Map by: dbrissett
Projection:
Source:

BOONE WATER MODEL Boone, IA FIGURE B
Max Pressures with Altitude Valves





BOONE WATER MODEL Boone, IA FIGURE C
Boone & Scenic Valley Railroad Water Main with
Boosted Daisy Zone Improvements




Project Number: BOONE 182275
Print Date: 10/14/2025

Map by: dbrissett
Projection:
Source:

BOONE WATER MODEL Boone, IA FIGURE D

North Transmission Main with
Boosted Daisy Zone Improvements





MEMORANDUM

TO: Perry Gjersvik, PE, City of Boone

FROM: Katie Kinsey, PE

McKenzie Hunt, PE

DATE: October 20, 2025

RE: Water Project Status Memo

SEH No. BOONE 182275

Short Elliott Hendrickson Inc. prepared a Preliminary Engineering Report (PER) evaluating the City of Boone's water system needs through 2044, excluding water distribution improvements. The PER accounts for the full buildout of the Daisy Brands (Daisy) facility by 2032. Since the PER was submitted, additional projects have emerged that also require consideration and implementation. A brief description of each project is provided below, along with a summary table at the end outlining the estimated costs associated with each project.

RECOMMENDED PROJECTS

Jordan Aquifer Wells

The Preliminary Engineering Report (PER) initially identified the Jordan Aquifer as a potential alternative water source for the City of Boone due to its lower nitrate concentrations compared to the existing alluvial aquifer. However, following consultation with a hydrogeologist and the Iowa DNR, it was determined that the Jordan Aquifer could not provide sufficient yield to meet the City's projected water demands, rendering it an impractical option. Consequently, the focus shifted to designing and constructing a new well within the existing alluvial aquifer, referred to as Alluvial Well #30.

This approach is more cost-effective, as alluvial wells are shallower and less expensive to construct than Jordan Aquifer wells. Currently, only one well is proposed. Well #30 is located in an area with historically lower nitrate levels, and if those levels remain low, its addition will help reduce the nitrate concentration in the raw water supply. As water demand increases and additional wells are brought online, Well #30 will play a key role in maintaining water quality across the system.

Lime Softening Treatment Modifications

The PER outlined treatment modifications that would be necessary when the Jordan Aquifer was added as a new source water. Design work began with a preliminary pilot study, which was submitted to the lowa DNR for review and approval. However, following the submittal, the Jordan Aquifer Well project was deemed unfeasible due to insufficient water availability. As a result, this project will be removed from the Water System Expansion Projects, resulting in some cost savings. However, because preliminary design work had already begun, the City will not realize the full savings originally anticipated.

Clearwell Modifications

The PER recommended modifications to the clearwell (chlorine contact tank) to prevent flooding of the high service pump station during the rehabilitation of the ground storage reservoir. These changes involved lowering the water level in the chlorine contact tank. However, upon reviewing the water treatment plant plans, a bypass line was identified exiting the chlorine contact tank that can achieve the same outcome without altering any internal appurtenances. As a result, this project will be removed from the Water System Expansion Projects list, resulting in full cost savings.

Ground Storage Reservoir Rehabilitation

An evaluation was completed on the ground storage reservoir in October 2022 and identified several recommended repairs to enhance the structural integrity and functionality of the reservoir. Completing these repairs before Daisy comes online in August 2028 is critical, as the reservoir will be needed to support the increased demand on the distribution system.

High Service Pump Replacement

The water treatment plant currently operates with three high service pumps (HSPs), running two at a time while keeping the third as backup. This project proposes replacing all three pumps with four HSPs equipped with variable frequency drives (VFDs), allowing operators to run three pumps simultaneously and maintain one for redundancy. Completing this upgrade by 2030 is essential to meet future distribution system demands.

1 MG Elevated Storage Tank

Daisy has an instantaneous water demand that totals approximately 750,000 gallons. Without additional storage, this demand could significantly strain the distribution system. To address this, a new 1,000,000-gallon storage tank is proposed, which will not only meet Daisy's needs but also provide a buffer for other Daisy demands. It is essential that this tank is completed by August 2028, when Daisy comes online, to ensure adequate capacity and prevent disruptions to the distribution system.

Greene Street Tower Altitude Valve Replacement

The existing Greene Street Tower currently operates using an altitude valve to regulate its high water level. However, City staff have experienced ongoing issues with the valve not functioning as intended. Hydraulic modeling has shown the Greene Street Tower to be obsolete due to minimal cycling and potential water age issues. As a result, this project will be removed from the Water System Expansion Projects list, resulting in full cost savings.

Alluvial Well #30

As noted in the Jordan Aquifer Wells project, this initiative replaces that original concept. One new well has been designed and will be constructed to draw additional source water from the alluvial aquifer. It is anticipated that this well will have low nitrate levels, which will benefit the City's blending strategy during periods of elevated nitrates in other wells. To meet water demands when Daisy comes online in August 2028, it is critical that this well be completed beforehand.

Sodium Hypochlorite Bulk Feed System

During the preliminary design phase for the high service pump replacement project, it was determined that the existing sodium hypochlorite feed system is undersized for system demands beginning in 2028. In order to adequately supply the system with disinfected water the sodium hypochlorite feed system will need to be upsized. The existing sodium hypochlorite room is undersized for the necessary storage and does not provide the space for required operator safety measures. It is recommended to construct an

Memorandum October 20, 2025 Page 3

addition to the high service pump building to house a bulk storage tank, feed pumps, and necessary safety equipment.

Generator Replacement

During the preliminary design phase for the high service pump improvements project, it was determined that the existing generator is undersized for the power demands beginning in 2029. In order to provide backup power for the water treatment plant, necessary wells, and high service pumps the generator will need to be upsized. It is recommended to upsize the existing generator with two 600 kW generators to meet system demands by 2029.

Water Main Upgrades – Boone & Scenic Valley Railroad Water Main and Piping Changes at W 12th Street and Coal Road

Hydraulic modeling of the City of Boone's water distribution system identified several key water main upgrades required prior to the Daisy facility becoming operational in August 2028. One of the most critical improvements is the construction of the Boone & Scenic Valley Railroad Water Main, which will convey water from a large main that crosses the Union Pacific Railroad directly to the Industrial Tower. This connection will help synchronize the floating levels of the Industrial and Clinton Street Towers, improving system balance. Another essential upgrade involves redesigning the water mains near W 12th Street and Coal Road. Once Daisy is online, elevated pressures are anticipated on the west side of the distribution system. Modifying the water main configuration in this area will help alleviate those pressures and maintain overall system stability.

Booster Station & Check Valve

Hydraulic modeling has shown that the Daisy site requires its own pressure zone due to its specific pressure needs. To achieve this, a booster station will be added at the new tower site to increase pressure to Daisy. Additionally, a check valve will be installed on Eastgate Drive to isolate the pressure zone and prevent backflow into the broader distribution system. This project must be completed before the new tower becomes operational to ensure proper functionality and pressure control.

Biological Nitrate Treatment Expansion

As noted in the Alluvial Well #30 project, a new alluvial well is proposed to be constructed with the intent being to drill a lower nitrate well to aid in the balance of incoming raw water nitrate levels. With elevated nitrate levels present in all wells during the summer months, the project team preliminarily explored reverse osmosis and ion exchange for nitrate removal. Both of these technologies produce waste streams that are difficult to treat with the existing configuration of the water treatment plant waste disposal. The existing waste stream from the water treatment plant goes to the lime waste ponds and then to the Des Moines River. The waste streams associated with ion exchange and reverse osmosis contain contaminants like chloride and nitrate at levels higher than the approved NPDES permit. To avoid these waste streams and provide nitrate removal biological nitrate treatment was explored.

Biological denitrification treatment has the capacity to reduce nitrate concentrations to levels established by the City through integration with the existing water treatment infrastructure. The U.S. Environmental Protection Agency (EPA) has set the Maximum Contaminant Level (MCL) for nitrates at 10 mg/L. With the anticipated increase in water demand associated with the commissioning of the Daisy facility, raw water nitrate concentrations are projected to range between 7.0 and 10 mg/L during the summer months. As current nitrate levels remain below the EPA's regulatory threshold of 10 mg/L, the City of Boone is not presently required to implement additional nitrate treatment measures.

Memorandum October 20, 2025 Page 4

Alluvial Well #31

A supplemental alluvial well may be designed and constructed to extract additional source water from the alluvial aquifer. The primary objective of this well is to provide a water source with low nitrate concentrations, thereby enhancing the City's blending strategy during periods of elevated nitrate levels in existing wells. A comparative evaluation of constructing an additional alluvial well versus implementing a nitrate treatment system should be conducted when nitrate concentrations exceed regulatory or operational thresholds.

Water Main Upgrades – North Transmission Main and Industrial Tower Altitude Valve

Hydraulic modeling conducted for the distribution system identified a key water main upgrade that will provide operators with a redundant water main from the water treatment plant to the east side of town, increasing system reliability. This water main also supports future expansion by enabling the addition of new water users on the north and east sides of town. Additionally, to prevent the Industrial Tower from overflowing, an altitude valve will need to be installed at the Industrial Tower.

ESTIMATED TOTAL PROJECT COSTS FOR RECOMMENDED PROJECTS

PER Recommended P	rojects	Current Project List		
Project Description	Total Cost	Project Description	Total Cost	
Jordan Aquifer Well (2EA)	\$3,112,560	Alluvial Well #30 (Design Complete)	\$1,101,480	
Lime Softening Treatment Modifications	\$720,720	Not needed	\$17,000	
Clearwell Modifications	\$98,868	Not needed		
Ground Storage Reservoir Rehabilitation	\$1,128,361	Ground Storage Reservoir Rehabilitation (Design Complete)	\$1,605,582	
High Service Pumps Replacement	\$957,330	High Service Pump Replacement (Design Complete)	\$1,673,950	
1 MG Elevated Storage Tank	\$4,791,600	1 MG Elevated Storage Tank	\$4,791,600	
Greene Street Tower Altitude Valve Replacement	\$71,280	Not needed		
		Sodium Hypochlorite Bulk Feed System	\$900,000	
		Generator Replacement	\$700,000	
		Water Main Upgrades - Boone & Scenic Valley Railroad Water Main Piping Changes at W 12th St & Coal Rd	\$2,800,000	
		Booster Station & Check Valve	\$700,000	
Total Cost	\$10,880,719	Total Cost	\$14,289,612	
		Projects On Hold		
		Biological Nitrate Treatment Expansion	\$12,000,000	
		Alluvial Well #31	\$1,500,000	
		Water Main Upgrades - North Transmission Main Industrial Tower Altitude Valve	\$8,600,000	

AUGUST 2025

City of Boone, Iowa

Water & Wastewater Treatment Facilities, Storage, and Lift Stations Monthly Operations & Maintenance Report

Prepared by:



1406 Central Avenue Fort Dodge, IA 50501 (515) 269-2338 Prepared For:



923 8th Street Boone, IA 50036 (515) 432-4211 August 2025

City of Boone Ondrea Elmquist, City Administrator 923 8th Street Boone, IA 50036

August Monthly Water & Wastewater Operations Report

Dear Ms. Elmquist:

In accordance with contract requirements, we are pleased to provide the following monthly report for August 2025. Below is a list of the significant events that occurred during the month:

SUBMITTED TO: Ondrea Elmquist, City Administrator

Utility Committee and City Council, City of Boone Aaron Voss, U.S. Water Services Corporation

We appreciate the opportunity to be of service to the City of Boone. We are available to discuss this report, or any other aspect of our operations, at your convenience. Should you have any questions or need additional information, please do not hesitate to contact us.

Sincerely,

J.D. Roberts, Water Environment Plant Supervisor USW Utility Group (712) 259-0805 JRoberts@USWaterCorp.net Dave Moore, Water Works Supervisor USW Utility Group (515) 230-3130 DMoore@USWaterCorp.net

Water Treatment Facility

F	inished Wa	ter Monthly Flows and Hard	ness
		August-2024	August-2025
Water	Units		
Average Daily Pumped	gallons	1,833,000	1,781,000
Maximum Daily Pumped	gallons	2,238,000	1,999,000
Minimum Daily Pumped	gallons	1,564,000	1,491,000
Hardness			
Hardness - Avg Raw	grains	19.9	20.2
Hardness - Avg Finish	grains	8.6	9.0
Iron mg/l			
Avg Raw	mg/L	.01	.01
Avg Finish	mg/L	.01	.01
Fluoride mg/l			
Avg Raw Fl.	mg/L	.47	.47
Avg Finish Fl.	mg/L	.70	.70

Water Storage

During the month of August, Greene Street, Industrial Park and Clinton Street Towers were in service as well as the 2-million-gallon reservoir and 550,000-gallon contact basin for a total of 4,150,000-gallons of storage.

Maintenance Report

During the month of August, the following tasks were completed:

- Cleaned pipping and adjusted altitude valve at pump station
- SCADA issues were fixed
- Repaired plugged tubing on Pump Station Chorine analyzer
- Sprayed for weeds around buildings and fence lines
- Unplugged Lime Pond drain lines

- Changed oil in the City's Ford F250 truck
- Cleaned out lime slurry troughs
- Washed trucks and tractors
- Mowed main plant, pump Station, water towers and well fields
- Mowed around lime ponds
- Verified all five turbidity meters weekly
- Calibrated all five turbidity meters
- Cleaned and verified calibration on all four CL-17 chlorine analyzers weekly
- Cleaned chlorine injector at pump station
- Replaced rooftop dehumidifier filters
- Misc. cleaning around water plant

Current & Planned Projects

During the month of September, the following tasks are planned:

- Change oils in backwash pumps and High Service Pumps
- Continue with miscellaneous yard work
- Serviced Claricone #1
- Serviced Slaker #1

Health & Safety

There were no safety violations to report for the current month.

The subjects of the weekly safety training were:

- 1. Climb Onto Ladder Safety.
- 2. Heat Illness.
- 3. Hand Safety.
- 4. Safety Data Sheets.
- 5. Arc Flash/Arc Blast Awareness and Safety.

Regulatory Reports

See attached documents

WASTEWATER

Wastewater Treatment Facility

	Wastewater Treatment Facilit	ty Flows	
	Plant Influent	Plant Effluent	Units
Total	134.93	•	MGD
Average per day	4.35	•	MGD
Minimum	1.99	•	MGD
Maximum	12.92	•	MGD

			Wast	ewater Inf	luent & Effluent	Quality		
	Influe	ent	Effluent	:				
Parameter	Daily Ave MG/L	Daily Ave LBS/Day	Daily Max MG/L	Permit Daily MG/L Limit	7 Day Max Ave MG/L	Permit 7 Day Max Limit	30 Day Average	Permit 30 Day Ave
BOD ₅	57	1628	•	•	•	•	•	•
CBOD ₅	•	•	4	•	4	40	3.1	25
Suspended solids	84.7	2673	8	•	4.75	45	4.1	30
Nitrogen Ammonia	6.1	169	.241	14.70	.135	•	.108 MG/L	2.4 MG/L
Nitrate Nitrogen	•	•	522 LBS/Day	1075 LBS/Day	522 LBS/Day	•	•	657 LBS/Day
Dissolved Oxygen	•	•	8.9	>5.0	8.68	•	8.22	>5.0
рН	7.42	•	8.0	6.5 to 9 STD Units	8.0	•	7.93	6.5 to 9 STD Units

ND= No Detection

• = No limit set

Solids Inventory

During the month of August, we pressed one day (12,000 gallons) and hauled 7.90 wet tons.

• Solids Inventory:

Stable but not improving.

Inventory is currently ~100,000 lbs, which is 2x the normal operating mass.

Volatile Solids (VS):

Currently at \sim 54%, up 1% over the past 30 days — this indicates a slow recovery in microbial activity or health.

Flows and Loadings:

Back to normal, which should help stabilize the system further.

Reseeding:

Still an option — on standby if further biological recovery stalls or regresses

Lift Stations

All lift stations are inspected at least twice per week to ensure proper operations. Airport Road Lift Station pump #1 does not keep a prime. Electric Pump and Iowa Pump have both provided repairs, but pump continues to fail. This station is on the R&R list for replacement.

• Lift Station pumps were inspected August 28, 2025.

Linn Street Lift Station – Pump 1:

Pump 1 was pulled and taken to Iowa Pump for further inspection. The Ohms readings were outside the normal range, prompting a more detailed evaluation by their team.

Snedden Drive Lift Station – Pump 1:

lowa Pump was initially able to get Pump 1 operational. However, the following day, the pump lost its prime and is currently out of service.

Maintenance Report

64 - (Sixty-Four) Preventive Maintenance Work orders Completed

- 8-6-25: Sludge Pump 2 gasket replacement
- 8-6-25: Raised both entrance gates 6"
- 8-19-25: Updated SC200 Controller and LDO Probes for the VLR
- 8-20-25: Replaced motor assembly for ISCO Influent Sampler
- 8-20-25: Built a Winterization Storage for UV Sleeves and Bulbs
- 8-21-25: Emptied and Inspected the East Digester. Clean out diffusers that were plugged
- 8-28-25: Tree and Brush removal on west side of plant.

Current & Planned Projects

- Roof Replacements- (Waiting on Manufacturer for safety Guiderail)
- In-plant Lift Station-(Currently in Engineering)
- Preliminary Screen Install-(Awarded to Shank Construction)
- North Clarifier Rehabilitation-Story Construction September

Health & Safety

There were no safety violations to report for the current month.

The subjects of the monthly safety training were:

- Arc Flash/Arc Blast Awareness and Safety
- Heat Illness
- Hackers that use social engineering don't hack computers—they hack people
- Hand Safety
- Phishing Types
- Safety Data Sheets
- Security Awareness Training (SAT) program

Regulatory Reports

See attached documents

SURFACE WATER/INFLUENCED GROUNDWATER MONTHLY OPERATION REPORT IOWA DNR WATER SUPPLY SECTION Basic Information S/EP #: 1 MONTH: August SYSTEM NAME: Boone Water Works PWSID #: 0819033 YEAR: 2025 **Pumpage** Operating Fluoride Chlorine Residual CT Cl2 Hours Source/Entry Point (S/EP) Distribution Used D Ratio of То Highest Rawin Specify Lowest Than CT Svstem ir Hours of Quantity Finished Number Measured Number With Measure 1,000s Free (F) /leasured 0.3 mg/L Obtaine 1,000s Treatment Used in of Tests Residual Residual Water Undetected Gallons or Total Residua Free Tests Taken lbs. Per Day (T) (mg/L) or (mg/L) Per Day Per Day (mg/L) Required Total 2,085 1,628 17.50 28 0.69 "C" (F) 0.28 0 4.7 34 0.28 2 2,010 1.608 17.00 28 0.72 (F) 1.86 0 0.26 0 0.26 4.9 33 18.00 3 2,139 1,752 0.73 (F) 2.00 0 0.26 0.26 36 30 "C" 0 4.1 4 2,496 1,999 21.50 34 0.70 "C" (F) 2.09 0 0.29 0.29 3.5 40 1 0 0.69 0.32 5 2,430 1,947 20.75 2.09 0.32 4.0 42 36 "C" (F) 0 0.35 6 1,736 0.68 "C" 2.33 0 0.35 36 2,153 18 50 28 (F) 6 0 4.9 7 2,114 1,682 18.00 30 0.70 "C" (F) 2.23 0 1 0.38 0 0.38 5.0 38 8 2,389 1,937 20.50 0.73 0 1 0.43 0 0.43 4.7 38 33 "C" (F) 2.31 9 16.50 0.70 1,886 1,491 27 "C" (F) 2.35 0.53 0 0.53 6.1 30 19.25 10 2,218 1,811 30 0.65 "C" (F) 2.52 0 1 0.55 0 0.55 5.1 37 1,715 18.25 0.69 2.23 0.57 0.57 11 2.116 30 "C" (F) 0 6 0 5.2 36 1,665 17.75 0.65 "C" 2.25 0 1 0.62 0.62 5.5 38 12 2.071 29 (F) 0 1,832 19.00 31 0.62 "C" (F) 1 92 0 1 0.65 0 0.65 49 40 13 2.237 "C" 1 14 2,328 1,876 20.00 32 0.73 (F) 2.14 0 0.70 0 0.70 4.8 41 15 1,766 18.75 0.73 2.11 0 1 0.73 0.73 5.0 39 2,188 33 "C" (F) 0 16 2,232 1,779 19.25 30 0.70 (F) 2.38 0 1 0.74 0 0.74 4.7 34 17 2,441 1,970 21.00 34 0.74 "C" (F) 2.54 0 0.72 0 0.72 4.2 40 18 2,191 1,764 20.00 30 0.71 (F) 2.09 0 0.69 0.69 4.7 36 "C" 1 0 19 1,685 18.50 0.70 2.23 0 0.70 0.70 37 2,132 28 "C" (F) 0 5.1 20 1 780 19 25 0.73 2 10 0 0.67 0.67 5.0 34 2 2 1 8 32 "C" (F) 1 0 21 0.68 0.69 0.69 37 2,185 1,721 18.75 30 "C" (F) 2.16 0 1 0 5.3 22 2,163 1,733 18.50 30 0.71 "C" (F) 2.07 0 1 0.70 0 0.70 5.6 36 23 19.25 0.74 0 38 2,216 1,706 26 "C" (F) 2.03 0.70 0 0.70 5.1 24 2,323 1,803 20.00 34 0.70 "C" (F) 1.99 0 0.70 0 0.70 5.2 38 25 1,744 18.75 0.70 2.07 0.71 0 0.71 4.9 36 2.183 30 "C" (F) 0 26 2,330 1,844 19.75 28 0.73 "C" (F) 2.19 0 0.72 0 0.72 4.8 38 "C" 27 2 268 1,836 19 00 33 0.72 (F) 2.10 0 1 0.73 0 0.73 49 38 28 2,353 1,878 19.75 30 0.77 "C" (F) 2.06 0.77 n 0.77 48 42 "C" 0.77 29 2 3 1 6 1.880 195 32 0.70 (F) 2 18 0 1 n 0.77 5.0 40 30 2,287 1,842 19.50 35 0.65 (F) 2.29 0 0.79 0 0.79 5.4 38 1,789 18.75 32 0.74 0.83 40 68,926 55,199 590.75 953 41 0 1,160 Tota 2,223 1,781 19.18 37 31 0.70 Avg 2 496 1,999 21 50 36 0.77 0.83 42 0 Max Min 1.886 1.491 16.50 26 0.62 1.78 0.26 3.5 30 *If continuous monitoring of chlorine is provided, enter "C" in the space provided. I certify that I am familiar with the information contained in this report and that the information is true, complete, and accurate. DRC Operator's or Designee's Signature: David Moore Certificate #: 4108 Grade: IV Date: 9/4/2025

D Nt Re Tal	Fini	EP: #1 AME: B shed Wa Number of Readings >0.3 NTU	Highest Daily Reading (NTU)	Higi Conse Resull NTU A After 4 From St Back	hest ecutive ts >0.5 nytime Hours art Up or	Daily Highest (NTU)	PWSI # of Consec	D#: 0	y Data 081903 #	Page 3	LY SE			Augu	st	•	YEAR:	2025		
D Nt Re Tal	Fini Number of leadings aken ** 17 18 17 19 21 21 19 18	Number of Readings >0.3 NTU	Highest Daily Reading (NTU)	Higl Conse Result NTUA After 4 From St	hest ecutive ts >0.5 nytime Hours art Up or	Daily Highest	# of Consec	D# : 0)81903 #	3		МС	ONTH:	Augu	st	,	YEAR:	2025		
D Nt Re Tal	Fini Number of leadings aken ** 17 18 17 19 21 21 19 18	Number of Readings >0.3 NTU	Highest Daily Reading (NTU)	Higl Conse Result NTUA After 4 From St	hest ecutive ts >0.5 nytime Hours art Up or	Daily Highest	# of Consec	Higl	#		Filtor F	МС	NTH:	Augu	st	,	YEAR:	2025		
D Nt Re Tal	Fini: Number of leadings aken ** 17 18 17 19 21 19 18	Number of Readings >0.3 NTU	Highest Daily Reading (NTU)	Higl Conse Result NTUA After 4 From St	hest ecutive ts >0.5 nytime Hours art Up or	Daily Highest	# of Consec	Higl	#		Filtor F	IVIC	/14 1 1 1.	rugu				2020		
A Y Re Tal 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	Number of steadings alken ** 17 18 17 19 21 19 18	Number of Readings >0.3 NTU	Highest Daily Reading (NTU)	Conse Result NTU A After 4 From St	hest ecutive ts >0.5 nytime Hours art Up or	Daily Highest	Consec					ffluont								
A Y Re Tal 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	of teadings aken ** 17 18 17 19 21 21 19	of Readings >0.3 NTU	Daily Reading (NTU)	Conse Result NTU A After 4 From St	hest ecutive ts >0.5 nytime Hours art Up or	Daily Highest	Consec			2	riitei E	muem		3			#	4		Raw
A Y Re Tal 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	of teadings aken ** 17 18 17 19 21 21 19	of Readings >0.3 NTU	Daily Reading (NTU)	Conse Result NTU A After 4 From St	ecutive ts >0.5 nytime Hours art Up or	Highest	Consec		hact	_		Higi				Hial	hest	•		Water
Y Re Tail 2	17 18 17 19 21 21 19	Readings >0.3 NTU	Reading (NTU)	NTUA After 4 From St	nytime Hours art Up or	Highest			ecutive		# of	Conse	cutive		# of	Conse	ecutive		# of	Turbidity
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	17 18 17 19 21 21 19	0 0	.02	From St	art Up or		Results	Result NTU A		Daily Highest	Consec Results	Result NTU A		Daily Highest	Consec Results	Result NTU A	ts >0.5 nytime	Daily Highest	Consec Results	(Highest Daily
2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	18 17 19 21 21 19	0					>1.0	After 4	Hours	(NTU)	>1.0	After 4		(NTU)	>1.0		Hours	(NTU)	>1.0	Reading NTU)
2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	18 17 19 21 21 19	0					NTU	Back	art Up or wash		NTU	From St Back			NTU	Back	art Up or wash		NTU	NTO)
3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	17 19 21 21 19 18	0	-	.01	.01	.02	0	.01	.01	.02	0	.02	.02	.03	0	.02	.02	.02	0	0.08
4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	19 21 21 19 18		.02	.02	.02	.02	0	.01	.01	.02	0	.02	.02	.02	0	.01	.01	.02	0	0.09
5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	21 21 19 18	0	.02	.02	.02	.02	0	.01	.01	.02	0	.02	.02	.03	0	.02	.02	.02	0	0.09
6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	21 19 18		.02	.01	.01	.02	0	.01	.01	.02	0	.02	.02	.02	0	.01	.01	.02	0	0.10
7 8 9 10 11 12 13 14 15 16 17 18 19 20	19 18	0	.02	.01	.01	.02	0	.01	.01	.02	0	.02	.02	.02	0	.01	.01	.02	0	0.09
8 9 10 11 12 13 14 15 16 17 18 19 20	18	0	.01	.02	.02	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.01	0	0.09
9 10 11 12 13 14 15 16 17 18 19 20		0	.02	.02	.02	.02	0	.02	.02	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.09
10	20	0	.02	.01	.01	.02	0	.01	.01	.02	0	.02	.01	.02	0	.01	.01	.02	0	0.09
11 12 13 14 15 16 17 18 19 20	20	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.11
12	16	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.11
13 14 15 16 17 18 19 20	21	0	.02	.03	.02	.03	0	.01	.01	.03	0	.01	.01	.02	0	.01	.01	.02	0	0.10
14 15 16 17 18 19 20	19	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.08
15 16 17 18 19 20	18	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.01	0	.01	.01	.02	0	0.08
16 17 18 19 20	19	0	.02	.02	.02	.03	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.01	0	0.08
17 18 19 20	20	0	.02	.02	.02	.02	0	.01	.01	.03	0	.01	.01	.02	0	.01	.01	.02	0	0.09
18 19 20	19	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.08
19 20	20	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.09
20	22	0	.02	.02	.02	.02	0	.01	.01	.02	0	.01	.01	.02	0	.02	.01	.02	0	0.09
_	19	0	.02	.02	.02	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.09
	20	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.11
_	20	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.09
	19	0	.02	.02	.02	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.08
	19 19	0	.02	.02	.02	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.09
	19	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.09
	19	0	.02	.03	.03	.02	0	.01	.01	.02	0	.01	.01	.01	0	.01	.01	.02	0	0.09
	20	0	.02	.03	.03	.03	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.09
	19	0	.02	.03	.02	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.09
_	20	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.07
_	20	0	.02	.02	.02	.03	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.01	0	0.08
_	20	0	.02	.02	.02	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.01	0	0.07
_	597	0					0				0				0				0	
Avg																				0.09
Max			.02			.03				.03				.03				.02		0.11
M in																				0.07
**If contin	nuo i s	onitoring o	f turbidity is	pro video	d, measu	rements r	nust be re	ecorded a	t equal tir	ne interv	als at leas	t once ev	ery four l	nours or l	no urly for	plants w/	pop. >100	,000.		
	nuous m																			
certify	nuous m	I am far	niliar wi	th the i	informa	ation c	ontaine	ed in th	is repo	ort and	that th	e infor	mation	is tru	e, com	plete, a	and ac	curate		
										DF	RC Ope	erator's	or De	signee	's Sign	ature:	Da	vid Mc	ore	
										Certific	ate #:	4108	(Grade:	IV		Date:	9/4/	2025	

						IOWA P	NR WATER	STIDDI V						
							asic Informat							
	S/EP:	#1					asic illioillat	IOII						
ystem Na		<i>m</i> 1				PWSID #:	810	1033		Month:	August		Year:	2025
yotem Na	Operating	Dum	page	Eluz	oride	Raw	010	Settled ⁻	Turbidity	WOITH.	August		ieai.	2020
D	Hours	i uiii	page	1100) i ue	Turbidity	(in	dividual sedir	-	ein)				
а	Number of		To System in	Quantity Used in		Highest Daily	Highest Daily	Highest Daily	Highest Daily	Highest Daily	Gallons Of			
у	hours the plant operated per day.	Rawin 1,000s Gallons Per Day	1,000s Gallons Per Day	lbs. or gal. (circle one)	Finished Water (mg/L)	Reading (NTU)	Reading Sed 1 (NTU)	Reading Sed 2 (NTU)	Reading Sed 3 (NTU)	Reading Sed 4 (NTU)	Liquid Chlorine Used 15%	Wett Well Residual		
1	17.50	2085	1628	28.00	0.69	0.08		0.94			19.40	0.48		
2	17.00	2010	1608	28.00	0.72	0.09		0.83			19.80	0.49		
3	18.00	2139	1752	30.00	0.73	0.09		2.30			20.40	0.44		
4	21.50	2496	1999	34.00	0.70	0.10		1.00			23.60	0.45		
5	20.75	2430	1947	36.00	0.69	0.09		1.51			23.00	0.50		
6	18.50	2153	1736	28.00	0.68	0.09		0.70			20.90	0.55		
7	18.00	2114	1682	30.00	0.70	0.09		1.19			19.60	0.54		
8	20.50	2389	1937	33.00	0.73	0.09		2.33			22.80	0.58		
9	16.50	1886	1491	27.00	0.70	0.11		0.82			17.80	0.57		
10	19.25	2218	1811	30.00	0.65	0.11		1.02			20.90	0.55		
11	18.25	2116	1715	30.00	0.69	0.10		1.33			19.80	0.57		
12	17.75	2071	1665	29.00	0.65	0.08		1.19			19.20	0.57		
13	19.00	2237	1832	31.00	0.62	0.08		1.83			21.00	0.55		
14	20.00	2328	1876	32.00	0.73	0.08		1.10			20.20	0.56		
15	18.75	2188	1766	33.00	0.73	0.09		0.65			20.50	0.54		
16	19.25	2232	1779	30.00	0.70	0.08		1.01			20.20	0.53		
17	21.00	2441	1970	34.00	0.74	0.09		0.71			22.90	0.52		
18	20.00	2191	1764	30.00	0.71	0.09		1.98			20.00	0.53		
19	18.50	2132	1685	28.00	0.70	0.09		1.20			20.00	0.53		
20	19.25	2218	1780	32.00	0.73	0.11		2.50			20.00	0.53		
21	18.75	2185	1721	30.00	0.68	0.09		0.91			19.10	0.56		
22	18.50	2163	1733	30.00	0.71	0.08		2.07			20.00	0.57		
23	19.25	2216	1706	26.00	0.74	0.09		1.18			19.80	0.55		
24	20.00	2323	1803	34.00	0.70	0.09		2.34			21.00	0.59		
25	18.75	2183	1744	30.00	0.70	0.09		1.26			20.20	0.53		
26	19.75	2330	1844	28.00	0.73	0.09		1.45			22.90	0.55		
27	19.00	2268	1836	33.00	0.72	0.09		0.82			22.20	0.54		
28	19.75	2353	1878	30.00	0.77	0.09		1.28			23.00	0.56		
29	19.50	2316	1880	32.00	0.70	0.07		2.17			22.80	0.57		
30	19.50	2287	1842	35.00	0.65	0.08		1.40			22.10	0.60		
31	18.75	2228	1789	32.00	0.74	0.07		1.28			21.80	0.56		
Total	591	68,926	55,199	953							646.90		0	0
Avg	19.06	2,223	1,781	30.74	0.70	0.09	#DIV/0!	1.36	#DIV/0!	#DIV/0!	20.87	0.54	#DIV/0!	#DIV/0
Max	21.50	2,496	1,999	36.00	0.77	0.11	0.00	2.5	0.0	0.00	23.60	0.60	0.00	0.00
M in	16.50	1,886	1,491	26.00	0.62	0.07	0.00	0.65	0.00	0.00	17.80	0.44	0.00	0.00
rtify that I	am familiar w	vith the inform	ation contain	ned in this rep	ort and that th	e information	is true, comp	lete, and acc	urate.					
					DRC Operato	r or Designe	e's Signature:	David Moore						
							Certificate #:	4108		Grade:	IV	Date:	9/4/2025	

	FLUC	RIDE	HARD	NESS	Р	Н	TOTA	L ALK	IRO	ON N	MANG	ANESE	ORTHO	H ₂ O	Cl ₂	NITE	RATE	RAW
DATE	RAW	FIN	RAW	FIN	RAW	FIN	RAW	FIN	RAW	FIN	RAW	FIN	PHOS	TEMP	FREE	RAW	FIN	TURB.
1		0.69	332	162	7.53	9.33	240	68	0.01	0.01			1.39	62	1.89	7.7	7.9	0.08
2		0.72	330	156	7.51	9.37	248	66	0.01	0.01			1.43	62	1.70	7.7	7.8	0.09
3		0.73	332	158	7.51	9.38	264	66	0.01	<.01			1.37	62	2.11	7.7	7.9	0.09
4		0.70	330	156	7.52	9.45	250	66	0.01	0.01			1.49	62	1.99	7.7	7.9	0.10
5		0.69	334	160	7.54	9.45	252	68	<.01	0.01			1.54	62	2.06	7.7	8.0	0.09
6		0.68	344	158	7.54	9.46	266	74	0.01	0.01			1.58	62	2.22	7.4	7.8	0.09
7		0.70	340	160	7.42	9.42	260	66	<.01	0.01			1.45	62	2.17	7.6	7.9	0.09
8		0.73	336	156	7.45	9.43	260	66	0.02	0.01			1.47	62	2.16	7.5	7.8	0.09
9		0.70	340	160	7.31	9.31	260	68	0.01	0.01			1.43	62	2.27	7.4	7.8	0.11
10		0.65	338	160	7.39	9.30	258	68	0.01	0.01			1.43	62	2.14	7.5	7.8	0.11
11		0.69	338	160	7.47	9.47	258	68	0.01	0.01			1.46	62	2.11	7.1	7.5	0.10
12		0.65	348	160	7.45	9.36	268	64	0.01	<.01			1.42	62	2.19	7.0	7.3	0.08
13		0.62	342	158	7.39	9.39	260	66	<.01	0.01			1.45	62	2.03	7.1	7.3	0.08
14		0.73	342	158	7.42	9.39	260	66	<.01	<.01			1.46	62	2.18	7.1	7.3	0.08
15	0.47	0.73	352	145	7.45	9.35	270	78	0.01	<.01	.35	.01	1.48	62	2.07	6.8	7.2	0.09
16		0.70	342	158	7.46	9.42	264	68	0.01	0.01			1.44	62	2.25	6.7	7.0	0.08
17		0.74	350	160	7.46	9.40	262	68	0.01	0.01			1.42	62	2.08	6.7	7.0	0.09
18		0.71	352	156	7.47	9.42	250	76	0.02	0.01			1.43	62	2.15	6.6	6.8	0.09
19		0.70	350	158	7.42	9.42	258	70	0.01	0.01			1.48	63	2.14	6.5	6.7	0.09
20		0.73	350	152	7.47	9.34	270	74	<.01	<.01			1.41	63	2.04	6.5	6.5	0.11
21		0.68	348	156	7.44	9.37	272	72	<.01	<.01			1.36	63	2.24	6.6	6.5	0.09
22		0.71	346	154	7.43	9.31	268	70	<.01	<.01			1.40	63	2.02	6.6	6.5	0.08
23		0.74	348	154	7.42	9.39	264	70	<.01	<.01			1.37	63	2.12	6.6	6.5	0.09
24		0.70	356	58	7.44	9.39	276	74	0.01	<.01			1.42	63	2.10	6.4	6.3	0.09
25		0.70	357	158	7.43	9.45	268	70	0.01	0.01			1.47	63	1.95	6.3	6.4	0.09
26		0.73	352	158	7.45	9.43	268	70	0.01	0.01			1.40	63	2.12	6.2	6.6	0.09
27		0.72	360	154	7.50	9.41	278	68	0.01	0.01			1.43	63	2.09	6.1	6.5	0.09
28		0.77	356	154	7.41	9.44	268	66	0.01	0.01			1.44	63	2.12	6.4	6.5	0.09
29		0.70	356	158	7.37	9.41	268	66	<.01	0.01			1.39	63	1.98	6.3	6.5	0.07
30		0.65	354	158	7.42	9.39	270	72	0.01	<.01			1.37	63	2.04	6.2	6.7	0.08
31		0.74	364	158	7.38	9.44	266	74	<.01	<.01			1.38	63	2.13	6.2	6.5	0.07
AVG		0.70	346	154	7.4	9.4	263	69	0.01	0.01	0.35	0.01	1.43	62	2.09	6.9	7.1	0.09
MAX		0.77	364	162	7.5	9.5	278	78	0.02	0.01	0.35	0.01	1.58	63	2.27	7.7	8.0	0.11
MIN		0.62	330	58	7.3	9.3	240	64	0.01	0.01	0.35	0.01	1.36	62	1.70	6.1	6.3	0.07

IOWA DEPARTMENT OF NATURAL RESOURCES NPDS REPORTING SYSTEM - DISCHARGE MONITORING REPORT

FACILITY INFORMATION

This form is valid 12/1/2024 to 11/30/2029

	Triis Torm is Valid 12/1/2024 to 11/30/2029
Facility Name:	BOONE CITY OF STP
Permit #:	0819001
Month/Year:	8 2025
Outfall #(s):	001 - DISCHARGE FROM AN ACTIVATED SLUDGE WASTEWATER TREATMENT FACILITY.
Operator Name:	John Roberts
Certification #:	10924
Phone #:	7122590805
Lab Cert. #:	156
Comments:	
	*Include Comments longer than 1000 characters in email
Signature:	
	John Roberts
	I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for known violations.

Permit # 0819001
Facility Name: BOONE CITY OF STP

Monthly Operation Report
IOWA DEPARTMENT OF NATURAL RESOURCES NPDS - Operation Permit System INFLUENT Data

Outfall #: 001 Month/Year: 8-2025

Month/Year:							RAW WASTE						
Parameter	FLOW	BO	D5	TS	SS	TO	T-N	Т	KN	PH	IOS	TEMP	PH
Units	MGD	MG/L	LBS/DAY	MG/L	LBS/DAY	MG/L	LBS/DAY	M G/L	LBS/DAY	M G/L	LBS/DAY	FAHRENHEIT	STD UNITS
Frequency	7/WEEK OR DAILY	2 TIMES PER WEEK	1 TIME PER WEEK	1 TIME PER WEEK	1 EVERY MONTH	1 EVERY MONTH	1 TIME PER WEEK	1 TIME PER WEEK	2 TIMES PER WEEK	2 TIMES PER WEEK			
Start Date													
End Date	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration
No Discharge													
LOQ													
Day: 1		27	1654.17228	35	2144.2974							66	7.4
2	5.943												
3	5.144												
4	4.623	45		43	1657.90026							67	7.3
5	4.284	47		52		10.3	368.004168	6.3	225.089928	1.7	60.738552	68	7.3
6	5.273	39	1715.09598	62	2726.56284							68	7.3
7	4.699											68	7.4
8	1.001											70	8
9	5.312												
10	12.922												
11	8.33			58	4029.3876							69	7.4
12						10.4	578.442384	4.5	250.28757	0.76	42.2707896	68	7.4
13		18	861.38856	18	861.38856							68	7.4
14		31	1247.19696									68	7.3
15												69	7.3
16													
17													
18	4.172			113	3931.77624							69	7.4
19						12.4	359.163768	11	318.61302	4.1	118.755762	70	7.5
20		52		91	2407.35768							70	7.4
21		60	1498.1976									69	7.5
22													7.4
23													
24	2.526			450	010101000								
25	2.354			158	3101.91288	00.50	500 4054050	00	F0F 0004	0.0	70.475000	66	7.4
26	2.342					30.52	596.1251856	30	585.9684	3.9	76.175892	66	7.5
27			0.10.1.0.1000	0.17								68	7.5 7.4
28		131		217	4015.90182							68	7.4
		120	2095.6752									69	7.5
30													
31 Total		C70	16285.96002	847	26734.3704	63.62	1901.735506	F4 0	1379.958918	40.40	297.9409956	1364	450
	4.352580645	570 57		84.7	26734.3704 2673.43704	15.905	475.4338764				74.4852489	1364	156 7.428571429
Monthly Avg. Daily Max.	4.352580645	131	2424.34626	84.7 217	4029.3876	30.52	596.1251856				74.4852489 118.755762	70	7.428571429
Daily Max.	12.922	18		18		10.32	359.163768					66	7.0
Max. 7/Avg.	6.914571429	131		187.5		30.52	596.1251856						7.3
wax. 7/Avg.	6.9145/1429	131	2424.34626	187.5	3558.90735	30.52	596.1251856	30	585.9684	4.1	118.755762	69.4	7.5

Permit#	0819001			ш	onthly Operation Res	port	1																			
	BOONE CITY OF STP				RTMENT OF NATURAL																					
acinty Name.	BOONE GITT OF 31F				- Operation Permit S																					
				NEDO	EFFLUENT Data	oysteili																				
Outfall #:	004				EFFLUENI Data		J																			
Month/Year:	8-2025																									
Mon. Point		IODS								_				AL EFFLUENT												
Parameter			TS	58		H3-N		ORIDE		(T)		13-N		Γ-N		NOLS		ios	TEMP	Р	5	TOX CER	TOX PIM	DO	PH	E COLI
Units	MG/L	LBS/DAY	MG/L	LBS/DAY	MG/L	LBS/DAY	MG/L	LBS/DAY	M G/L	LBS/DAY	MG/L	LBS/DAY	MG/L	LBS/DAY	M G/L	LBS/DAY	MG/L	LBS/DAY	FAHRENHEIT	MG/L	LBS/DAY	NO TOXICITY	NO TOXICITY	M G/L	STD UNITS	#/100 ML
Frequency	2 TIMES PER WEEK	2 TIMES PER WEEK	2 TIMES PER WEEK	2 TIMES PER WEEK	2 TIMES PER WEEK	2 TIMES PER WEEK	1 EVERY MONTH	1 EVERY MONTH	1 TIME PER WEEK	1 TIME PER WEEK	1 EVERY MONTH	1 EVERY MONTH	1 TIME PER WEEK	1 TIME PER WEEK	1 EVERY MONTH	1 EVERY MONTH	1 TIME PER WEEK	1 TIME PER WEEK	2 TIMES PER WEEK	1 TIME PER WEEK	1 TIME PER WEEK	1 EVERY 12 MONTHS	1 EVERY 12 MONTHS	2 TIMES PER WEEK	5 TIMES PER WEEK	GEO. MEAN 1/3 MON
Start Date																										
End Date	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration
Discharge																						06 - NOT REQ / MP	06 - NOT REQ / MP			06 - NOT REQ / MP
LOQ																										
Day: 1	3	183.79692	8	490.12512	0.24	4 14.7037536													67					8.9	9 8	В
2		000000000000000000000000000000000000000		8888888888888		888888888888		8888888888		88888888888		3838888888		989888888888		18888888888		00000000000000			38888888888					
3		100000000000000000000000000000000000000		8888888888888		888888888888	1	8888888888		88888888888		8888888888		888888888888		000000000000000000000000000000000000000		88888888888			188888888888					
4	3	115.66746	5	192.7791															68					8.7		
5	3	107.18568	4	142.91424	0.1	1 3.572856		000000000000000000000000000000000000000	0.0035	0.12504996			12.5	446.607		000000000000000000000000000000000000000	0.74	26.4391344	68	0.001	0.03572856			8.8	8 7.9	9
6	3	131.93046	2	87.95364	0.1														68					8.4		9
7		1888888888888		8888888888888	0.1	1 3.918966		88888888888		888888888888		88888888888		888888888888		88888888888		88888888888	68		88888888888			8.6	8 7.9	9
8					0.1	1 3.842238													70					8.6	6 8	В
9		1888888888888		8888888888888		1888888888888		88888888888		888888888888		88888888888		8888888888888		88888888888		888888888888			88888888888					
10																										
11		18888888888888	6	416.8332		18888888888888		88888888888		88888888888		8888888888		00000000000000		0000000000000		888888888888	69					8.8	8 8	В
12					0.	1 5.561946	84	4872 03484	0.0035	0.19488811	9.4	522 822924	10.3	572 880438	0.0192	1.067893632	0.52	28 9221192	68	0.001	0.05561946			81	8 /	R
11	3	143,56476	2	95,70984	0.		-				-								68					8.6	8 8	8
14	3	120.69648		000000000000000	0.	1 4.023216		00000000000		0000000000000		00000000000		00000000000000				0000000000000	68					8.4	4 8	B
15				8888888888888	0.1			88888888888		888888888888		0000000000000		00000000000000		88888888888		888888888888	68					8.0		9
16																			-							
17							+																+	+	+	
18			4	139.17792	0.1	1 3.479448		000000000000		0000000000000								00000000000000	70					8.1	1 79	9
10				100.11102	0.				0.0035	0.10137687			11.62	336,5712084			4.2	34 757784	70	0.001	0.02896482			8:		0
20	3	79.36344	2	52.90896				99999999999	0.0030	3.1013/08/		0000000000000	11.02	550.07 12004		0000000000000	1.4	34.707704	70	0.001	0.02090402			8.3		
21	3	74.90988		02.90090	0.			000000000000		0000000000000		000000000000		0000000000000		000000000000		00000000000000	70					8.		R
21		74.90300		000000000000000	0.			000000000000		222222222222				0000000000000				00000000000000	70	-			+	7.0		
22					0.	2.3/0228	-				-		-				-			-		-	+	7.3	0	
23		000000000000000000000000000000000000000				000000000000000000000000000000000000000	-	000000000000000000000000000000000000000		000000000000000000000000000000000000000	-	000000000000	_	00000000000000		0000000000000		000000000000000000000000000000000000000			000000000000000000000000000000000000000		+	+	+	+
24				98 1618			-		1											 			+	7.4	4 78	
25		000000000000000000000000000000000000000		98.1618	0.	1 1 953228	-	000000000000000000000000000000000000000	0.0035	0.06836298		000 0400	17 79	0.47 4700040		000000000000000000000000000000000000000		27 345192	68	0.001	0.01953228			7.4		0
26		12222222222222		88888888888888	0.		1	88888888888	0.0035	0.06836298	13	253.91964	17.79	347.4792612		88888888888	1.4	27.345192	67	0.001	0.01953228	-		7.5		9
27		74.02584		55.51938	0.			000000000000000000000000000000000000000		000000000000000000000000000000000000000		0000000000000		000000000000000		0000000000000		000000000000000	69		00000000000000			7.3	8 7.9	3
28	4		3	55.51938				33333333333		888888888888				******		888888888888			70				+	7.5	7.5	9
29	3	52.39188			0.1	1 1.746396	1												70					7.3	3 7.8	В
30					L																		4	1	1	-
31		100000000000000000000000000000000000000		000000000000000000000000000000000000000	0.1			000000000000000000000000000000000000000		000000000000000000000000000000000000000		2222233333		000000000000000000000000000000000000000		2222233333		000000000000000000000000000000000000000							1	
Total	31	1083.5328	41	1772.0832	2.04		84	4672.03464			22.4				0.0192		3.86		1374		0.13984512			172.0		
lonthly Avg.	3.1		4.1	177.20832	0.10736842		84	4672.03464	0.0035	0.12236448	11.2		13.0525		0.0192		0.965		68.7		0.03496128			8.219047619		3
Daily Max.	4	183.79692	8	490.12512	0.24		84	4672.03464			13	522.822924			0.0192			34.757784	70	0.001				8.9		В
Daily Min.	3	52.39188	2	52.90896	0.1			4672.03464	0.0035		9.4	253.91964			0.0192		0.52		67					7.3		В
Max. 7/Avg.	4	134.64513	4.75	256.27152	0.13	5 6.6483144	84	4672.03464	0.0035	0.19466811	13	522.822924	17.79	572.880438	0.0192	1.067893632	1.4	34.757784	69.6	0.001	0.05561946			8.68	8	В



1406 Central Avenue Fort Dodge, Iowa 50501 515-269-2338

 $w\ w\ w\ .\ U\ S\ W\ U\ t\ i\ l\ i\ t\ y\ G\ r\ o\ u\ p\ .\ c\ o\ m$

SEPTEMBER 2025

City of Boone, Iowa

Water & Wastewater Treatment Facilities, Storage, and Lift Stations
Monthly Operations & Maintenance Report

Prepared by:



1406 Central Avenue Fort Dodge, IA 50501 (515) 269-2338 Prepared For:



923 8th Street Boone, IA 50036 (515) 432-4211 September 2025

City of Boone Ondrea Elmquist, City Administrator 923 8th Street Boone, IA 50036

September Monthly Water & Wastewater Operations Report

Dear Ms. Elmquist:

In accordance with contract requirements, we are pleased to provide the following monthly report for September 2025. Below is a list of the significant events that occurred during the month:

SUBMITTED TO: Ondrea Elmquist, City Administrator

Utility Committee and City Council, City of Boone Aaron Voss, U.S. Water Services Corporation

We appreciate the opportunity to be of service to the City of Boone. We are available to discuss this report, or any other aspect of our operations, at your convenience. Should you have any questions or need additional information, please do not hesitate to contact us.

Sincerely,

J.D. Roberts, Water Environment Plant Supervisor USW Utility Group (712) 259-0805 JRoberts@USWaterCorp.net Dave Moore, Water Works Supervisor USW Utility Group (515) 230-3130 DMoore@USWaterCorp.net

Water Treatment Facility

F	inished Wa	ter Monthly Flows and Hard	ness
		September-2024	September-2025
Water	Units		
Average Daily Pumped	gallons	2.002,000	1,880,000
Maximum Daily Pumped	gallons	2,278,000	2,652,000
Minimum Daily Pumped	gallons	1,546,000	1,632,000
Hardness			
Hardness - Avg Raw	grains	19.2	20.6
Hardness - Avg Finish	grains	8.6	9.2
Iron mg/I			
Avg Raw	mg/L	.01	.02
Avg Finish	mg/L	.01	.01
Fluoride mg/l			
Avg Raw Fl.	mg/L	.52	.45
Avg Finish Fl.	mg/L	.82	.73

Water Storage

During the month of September, Greene Street, Industrial Park and Clinton Street Towers were in service as well as the 2-million-gallon reservoir and 550,000-gallon contact basin for a total of 4,150,000-gallons of storage.

Maintenance Report

During the month of September, the following tasks were completed:

- Repaired leaking ball valve at Greene Street Tower
- Cleaned and serviced wells #25 and #27
- Collected Nitrate samples from all 14 wells
- Rebuilt check valve on gas chlorine feed system
- Rotated lime slakers

- Rotated backwash pumps and blowers
- Repaired electrical issue with backwash pump #2
- Services US Water F150 truck
- Changed oil in backwash pumps #1 and #2
- Washed trucks and tractors
- Mowed main plant, pump Station, water towers and well fields
- Mowed around lime ponds
- Verified all five turbidity meters weekly
- Calibrated all five turbidity meters
- Cleaned and verified calibration on all four CL-17 chlorine analyzers weekly
- Cleaned and serviced chlorine injector at pump station
- Replaced rooftop dehumidifier filters
- Misc. cleaning around water plant

Current & Planned Projects

During the month of October, the following tasks are planned:

- Change oils in High Service Pumps
- Continue with miscellaneous yard work
- Service Claricone #1
- Service Slaker #1

Health & Safety

There were no safety violations to report for the current month.

The subjects of the weekly safety training were:

- 1. Trenching Safety
- 2. Biohazards
- 3. Laboratory Safety
- 4. Working On The Road
- 5. Eye Protection
- 6. First Aid Basics

Regulatory Reports

See attached documents

WASTEWATER

Wastewater Treatment Facility

	Wastewater Treatment Facilit	ty Flows	
	Plant Influent	Plant Effluent	Units
Total	46.12	•	MGD
Average per day	1.54	•	MGD
Minimum	1.185	•	MGD
Maximum	2.08	•	MGD

			Wastewa	ater Influe	ent & Efflu	ent Qualit	y	
	Influer	nt	Effluent					
Parameter	Daily Ave MG/L	Daily Ave LBS/Day	Daily Max MG/L	Permit Daily MG/L Limit	7 Day Max Ave MG/L	Permit 7 Day Max Limit	30 Day Average	Permit 30 Day Ave
BOD ₅	178.25	2278	•	•	•	•	•	•
CBOD ₅	•	•	3	•	3	40	3	25
Suspended solids	243	3116	8.0	•	5.5	45	3.11	30
Nitrogen Ammonia	19.8	244	.1	16.50	.1	•	.1 MG/L	1.5 MG/L
Nitrate Nitrogen	•	•	146 LBS/Day	1075 LBS/Day	•	•	•	657 LBS/Day
Dissolved Oxygen	•	•	8	>5.0	7.34	•	7.13	>5.0
рН	7.42	•	8.0	6.5 to 9 STD Units	7.76	•	7.72	6.5 to 9 STD Units

ND= No Detection

• = No limit set

Solids Inventory

During the month of September, we pressed two days (68,000 gallons) and hauled 25.40 wet tons.

Solids Inventory:

Improving Slowly

The Average Inventory for the month: 112,000 lbs, which is 2x the normal operating mass.

Volatile Solids (VS):

The average for the month: 55.5%, up 2.4% from August — this indicates a slow recovery in microbial activity or health.

Flows and Loadings:

Back to normal, which should help stabilize the system further.

Reseeding:

Still an option — on standby if further biological recovery stalls or regresses

Lift Stations

All lift stations are inspected at least twice per week to ensure proper operations. Airport Road Lift Station pump #1 does not keep a prime. Electric Pump and Iowa Pump have both provided repairs, but pump continues to fail. This station is on the R&R list for replacement.

Maintenance Report

45 - (Forty-Five) Preventive Maintenance Work orders Completed

- Fixed leak on VLR Blower 3
- Removed trees along West Fence Line
- Replaced Lab Refrigerator
- Story Construction Completed North Clarifier Drive

Current & Planned Projects

- Roof Replacements- Completed
- In-plant Lift Station-(Currently in Engineering)
- Preliminary Screen Install-(Awarded to Shank Construction)
- North Clarifier Rehabilitation-Completed

Health, Safety and Cybersecurity

There were no safety violations to report for the current month.

The subjects of the monthly safety training were:

- Material Storage & Handling
- Combatting Phishing
- Eye Protection
- Working on the Road
- Communication and Safety
- Laboratory Safety
- Biohazards
- Vishing
- Money Transfer Fraud
- Hazardous Substances: Incidental Spill Response

Regulatory Reports

See attached documents

SURFACE WATER/INFLUENCED GROUNDWATER MONTHLY OPERATION REPORT **IOWA DNR WATER SUPPLY SECTION** Basic Information S/EP #: 1 MONTH: September SYSTEM NAME: Boone Water Works PWSID #: 0819033 YEAR: 2025 **Pumpage** Operating Fluoride Chlorine Residual CT Cl2 Hours Source/Entry Point (S/EP) Distribution Used D Hours Less Ratio of Highest Raw in Specify Lowest Than CT System i Hours of Quantity Finished Number Measured lumber With 1,000s /leasured 0.3 mg/L Obtained Chlorine in 1,000s Treatment Used in of Tests Residual Undetected Residual Water Gallons or Total Residual Free Tests Taker nt Operatio (mg/L) Residual Per Day (T) (mg/L) СТ Per Day Per Day (mg/L) (mg/L) 1.5 mg/L Required Total 0.75 37 2,332 1,874 19.75 31 "C" (F) 2.34 0.82 0 0.82 4.9 2,305 1,882 19.50 30 0.72 "C" (F) 0 6 0.47 38 0 1.62 20.50 0.67 (F) 2.03 0.82 2,383 1,921 32 0.82 41 4.8 4 2,155 1,730 18.50 32 0.77 "C" (F) 2.11 0 1 0.91 0 0.91 5.4 35 0.67 5 2,313 1,855 20.25 "C" (F) 2.17 0.86 0.86 42 32 0 0 5.1 0.68 0.88 0.88 38 6 2.204 1,775 19.25 30 "C" (F) 2.17 0 0 5.3 2,360 1,914 20.75 34 0.64 "C" (F) 2.18 0 0.88 0 0.88 5.1 40 8 2,301 1,856 20.25 30 0.72 "C" (F) 2.15 0 0.88 0 0.88 5.1 35 1,885 21.00 30 0.60 "C" (F) 2.19 0 6 1.44 41 2,423 0.85 0 5.1 1,880 21.75 0.74 2.22 0.91 43 10 2.510 37 "C" (F) 0 0.91 0 4.8 11 1,916 21.50 37 0.74 "C" (F) 2.20 0 0.91 0 0.91 4.4 43 2,585 12 2,687 1,977 20.75 38 0.73 "C" (F) 2.08 0 1 0.90 0 0.90 4.7 44 0.80 13 2.613 2.003 20.00 "C" 1.93 0 0.89 0.89 4.5 45 36 (F) 14 2,652 21.25 38 0.89 "C" (F) 2.11 0 0.88 0 0.88 4.6 44 1,992 15 2,483 1,999 20.00 34 0.65 "C" (F) 2.06 0 0.83 0.83 3.8 43 16 2,212 1,815 17.75 31 0.71 "C" (F) 1.95 0 1 0.80 0.80 4.3 39 17 37 2,174 1,734 17.50 30 0.74 (F) 2.16 0.77 0.77 4.9 37 18 2,179 1,722 18.00 30 0.80 "C" (F) 2.05 0 0.76 0 0.76 4.5 19 16.25 37 2,055 1,632 0.74 (F) 2.16 0.77 0.77 5.0 30 "C" 0 0 20 0.76 37 2.034 1.655 16.25 27 0.73 "C" (F) 2.12 0 0.76 4.8 0 21 18.75 0.77 42 2.353 1.930 0.72 (F) 2.21 0 0.77 4.3 34 "C" 0 22 1,753 28 0.68 "C" (F) 2.23 0 0.79 0.79 4.6 39 2,181 18.75 0 23 2,213 1,787 19.25 0.79 "C" (F) 2.17 0 0.81 0.81 4.5 38 32 0 24 1,740 18.75 0.76 "C" 0.83 37 2,148 30 (F) 2.18 0 0.83 25 2,349 1,898 20.50 34 0.75 "C" (F) 2.12 0 0.83 0 0.83 4.2 40 26 2,266 1,780 19.75 31 0.73 "C" (F) 2.09 0 0.83 0 0.83 4.4 39 27 2.337 1.833 20.50 31 0.73 "C" (F) 2.21 0.82 0.82 4.0 45 28 2 656 2 194 0.72 "C" (F) 2 38 0 0.84 0 0.84 5 4 49 23 25 39 29 2 300 1 939 20.00 28 0.67 "C" (F) 1.89 0 0.83 0.83 7.3 42 1,872 (F) 40 30 2 298 20.25 32 0.72 0.85 0.85 69,401 56,403 590.50 968 40 0 1,207 Tota 2,313 1,880 19.69 32 0.73 40 Avg 2,687 2.652 23.25 39 0.89 0 1.62 49 0.47 35 *If continuous monitoring of chlorine is provided, enter "C" in the space provided. I certify that I am familiar with the information contained in this report and that the information is true, complete, and accurate. DRC Operator's or Designee's Signature: David Moore Certificate #: 4108 Grade: 10/2/2025

D Nu Re Tal	Finis	EP: #1 ME: B Shed Wa Number of Readings >0.3 NTU				IC	DWA D	urbidit		SUPP Page		CTION								
D Nu Re Tal	Finish lumber of eadings aken **	Number of Readings	ater Highest						y Data	Page	1 of 1									
D Nu Re Tal	Finish lumber of eadings aken **	Number of Readings	ater Highest				PWSI	D # 3												
D Nu Re Tal	Finis lumber of eadings aken **	Number of Readings	ater Highest				PWSI			_				α .				2025		
A Y Re Tal	lumber of eadings aken **	Number of Readings	Highest	Hia	ŧ			υ#: ()81903	3				Septe	mber		YEAR:	2025		
A Y Re Tal	of eadings iken **	of Readings		Hia	#			Filter Effluent					Bow.							
A Y Re Tal	of eadings iken **	of Readings		Hia		<u>‡1</u>				2				3				4		Raw Water
2	20		Reading (NTU)	Conse Result NTU A After 4	ts >0.5 Inytime Hours art Up or	Daily Highest (NTU)	# of Consec Results >1.0 NTU	Conse	ts >0.5 nytime Hours art Up or	Daily Highest (NTU)	# of Consec Results >1.0 NTU	High Conse Result NTU A After 4 From Sta Backy	cutive s >0.5 nytime Hours art Up or	Daily Highest (NTU)	# of Consec Results >1.0 NTU	Conse Result NTU A After 4 From Sta	hest ecutive ts >0.5 .nytime Hours art Up or wash	Daily Highest (NTU)	# of Consec Results >1.0 NTU	Turbidity (Highest Daily Reading NTU)
3		0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.10
	20	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.01	0	.01	.01	.02	0	0.09
4	20	0	.01	.02	.02	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.01	0	0.08
	21	0	.02	.02	.01	.02	0	.01	.01	.02	0	.02	.01	.02	0	.01	.01	.02	0	0.13
5	19	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.14
6	20	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.11
7	19	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.11
8	21	0	.02	.02	.02	.02	0	.02	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.12
9	20	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.01	0	.01	.01	.02	0	0.38
10	21	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.01	0	.01	.01	.02	0	0.09
11	21	0	.01	.02	.02	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.01	0	0.09
12	22	0	.02	.02	.02	.02	0	.01	.01	.01	0	.01	.01	.02	0	.01	.01	.02	0	0.08
13	21	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.24
14	21	0	.02	.02	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.13
15	21	0	.01	.02	.02	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.01	0	0.09
16	19	0	.02	.02	.02	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.09
17	18	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.01	0	.01	.01	.02	0	0.11
18	18	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.01	0	.01	.01	.02	0	0.09
19	18	0	.02	.02	.02	.03	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.09
20	17	0	.02	.02	.03	.03	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.01	0	0.10
21	16	0	.01	.01	.01	.02	0	.01	.01	.01	0	.01	.01	.02	0	.01	.01	.02	0	0.09
22	19	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.01	0	0.08
23	19	0	.02	.02	.02	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.07
24	20	0	.02	.02	.02	.03	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.08
25	19	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.08
26	21	0	.02	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.01	0	.01	.01	.02	0	0.09
27	20	0	.02	.02	.02	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.02	.02	0	0.08
28	21	0	.02	.02	.02	.03	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.08
29	24	0	.01	.01	.01	.01	0	.01	.01	.01	0	.01	.01	.01	0	.01	.01	.01	0	0.07
30	20	0	.02	.02	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	.01	.01	.02	0	0.08
Total	596	0					0				0				0				0	
Avg																				0.11
Max			.02			.03				.02				.02				.02		0.24
Min																				0.07
**If continu	nuous mo	nitoring of	turbidity is	provided,	measure	ements mi	ust be rec	orded at e	equal time	intervals	at least o	once every	y four ho	urs or hou	irly for pla	nts w/pop	o. >100,00	00.		
I certify	y that	I am far	miliar wi	th the	inform	ation c	ontaine	ed in th	nis repo	ort and	that th	ne infor	matio	n is tru	e, com	plete,	and ac	curate). 	
										DF	RC Ope	erator's	or De	signee	's Sigr	nature:	Da	vid Mo	ore	
										Certific				Grade:	IV			10/2		

						IOWA D	NR WATER	SUPPLY						
							asic Informat							
	S/EP:	#1												
ystem Na	ime:					PWSID #:	819	033		Month:	September		Year:	2025
	Operating	Pum	page	Fluc	ride	Raw		Settled ¹	Turbidity					
D	Hours					Turbidity	(in	dividual sedir	nentation ba	sin)				
а	Number of hours the plant	Raw in 1,000s	To System in	Quantity Used in	Finished Water	Highest Daily	Highest Daily	Highest Daily	Highest Daily	Highest Daily	Gallons Of	Wett Well		
У	operated per	Gallons Per Day	1,000s Gallons Per Day	lbs. or gal. (circle one)	(mg/L)	Reading (NTU)	Reading Sed 1 (NTU)	Reading Sed 2 (NTU)	Reading Sed 3 (NTU)	Reading Sed 4 (NTU)	Liquid Chlorine Used 15%	Residual		
1	day. 19.75	2332	1874	31.00	0.75	0.10	1 (1410)	0.91	3 (1410)	4 (1410)	22.90	0.60		
2	19.75	2305	1882	30.00	0.75	0.10		0.91			23.00	0.58		
3	20.50	2383	1921	32.00	0.72	0.08		1.75			23.10	0.56		
4	18.50	2155	1730	32.00	0.77	0.13		1.12			21.00	0.57		
5	20.25	2313	1855	32.00	0.67	0.13		0.53			23.00	0.56		
6	19.25	2204	1775	30.00	0.68	0.14		0.67			21.80	0.57		
7	20.75	2360	1914	34.00	0.64	0.11		1.20			22.70	0.59		
8	20.75	2301	1856	30.00	0.72	0.11		2.65			21.80	0.58		
9	21.00	2423	1885	30.00	0.60	0.12		2.09			21.30	0.58		
10	21.75	2510	1880	37.00	0.74	0.09		0.78			22.00	0.57		
11	21.73	2585	1916	37.00	0.74	0.09		1.72			23.00	0.51		
12	20.75	2687	1977	38.00	0.73	0.08		0.76			21.90	0.60		
13	20.00	2613	2003	36.00	0.80	0.24		2.94			23.80	0.51		
14	21.25	1992	2652	38.00	0.89	0.13		2.78			23.10	0.43		
15	20.00	2483	1999	34.00	0.65	0.09		0.84			24.00	0.46		
16	17.75	2212	1815	31.00	0.71	0.09		1.59			20.90	0.46		
17	17.50	2174	1734	30.00	0.74	0.11		1.35			20.40	0.52		
18	18.00	2179	1722	30.00	0.80	0.09		1.30			20.10	0.47		
19	16.25	2055	1632	30.00	0.74	0.09		0.91			19.00	0.50		
20	16.25	2034	1655	27.00	0.73	0.10		0.97			19.30	0.46		
21	18.75	2353	1930	34.00	0.72	0.09		2.56			23.00	0.46		
22	18.75	2181	1753	28.00	0.68	0.08		1.56			20.80	0.47		
23	19.25	2213	1787	32.00	0.79	0.07		0.90			20.60	0.45		
24	18.75	2148	1740	30.00	0.76	0.08		0.91			21.00	0.45		
25	20.50	2349	1898	34.00	0.75	0.08		1.10			22.50	0.44		
26	19.75	2266	1780	31.00	0.73	0.09		0.84			21.00	0.43		
27	20.50	2337	1833	31.00	0.73	0.08		0.40			21.50	0.40		
28	23.25	2656	2194	39.00	0.72	0.08		0.82			25.60	0.63		
29	20.00	2300	1939	28.00	0.67	0.07		0.99			22.20	0.78		
30	20.25	2298	1872	32.00	0.72	0.08		2.56			21.10	0.67		
Total	591	69,401	56,403	968							657.40	0	0	0
Avg	19.05	2,239	1,819	31.23	0.70	0.11	#DIV/0!	1.35	#DIV/0!	#DIV/0!	21.91	0.53	#DIV/0!	#DIV/
Max	23.25	2,687	2,652	39.00	0.89	0.38	0.00	2.9	0.0	0.00	25.60	0.78	0.00	0.00
Min	0.00	0	0	0.00	0.00	0.00	0.00	0.40	0.00	0.00	19.00	0.40	0.00	0.00
ertify that I	I am familiar w	ith the inform	ation contain	ed in this rep	ort and that th	e information	is true, comp	elete, and acc	urate.					
					DRC Operato	r or Designe	e's Signature:	David Moore						
							Certificate #:	4108		Grade:	IV	Date:	10/2/2025	
							Continuate #.			Grade.		Date.	. 51212025	

	FLUC	RIDE	HARD	NESS	Р	Н	TOTA	L ALK	IR	ON	MANG	ANESE	октно	H ₂ O	Cl ₂	NITE	RATE	RAW
DATE	RAW	FIN	RAW	FIN	RAW	FIN	RAW	FIN	RAW	FIN	RAW	FIN	PHOS	TEMP	FREE	RAW	FIN	TURB.
1		0.75	358	158	7.5	9.6	266	72	0.02	<.01			1.39	63	2.04	5.9	6.3	0.10
2		0.72	358	160	7.5	9.6	266	70	<.01	0.01			1.44	63	1.98	5.9	6.3	0.09
3		0.67	354	160	7.5	9.4	278	76	0.01	<.01			1.44	63	2.04	5.7	6.0	0.08
4		0.77	358	160	7.4	9.4	272	70	0.01	0.01			1.45	63	2.28	5.5	6.1	0.13
5		0.67	354	160	7.5	9.4	280	76	0.02	<.01			1.43	64	2.22	5.7	6.0	0.14
6		0.68	352	156	7.5	9.4	284	68	0.01	<.01			1.45	63	2.26	5.4	5.6	0.11
7		0.64	356	156	7.5	9.4	276	76	0.01	<.01			1.42	63	2.35	5.3	5.4	0.11
8		0.72	362	154	7.5	9.4	284	80	0.01	<.01			1.43	63	2.25	5.2	5.2	0.12
9		0.60	378	158	7.4	9.4	278	78	0.15	<.01			1.44	64	2.27	5.5	5.2	0.38
10		0.74	364	166	7.5	9.4	270	84	0.01	<.01			1.43	64	2.32	5.5	5.4	0.09
11		0.74	352	158	7.5	9.4	276	72	0.01	<.01			1.49	65	1.83	5.2	5.3	0.09
12		0.73	352	154	7.5	9.5	276	70	0.01	<.01			1.40	65	2.10	5.0	5.3	0.08
13		0.80	350	162	7.5	9.3	274	76	0.14	<.01			1.45	65	2.23	4.5	4.9	0.24
14		0.89	362	162	7.5	9.4	272	72	0.04	0.01			1.48	64	2.05	4.4	4.7	0.13
15	0.45	0.65	352	154	7.6	9.5	272	78	0.02	0.01	.44	.01	1.45	64	2.10	4.3	4.5	0.09
16		0.71	352	158	7.4	9.5	272	72	0.02	0.01			1.41	64	2.10	4.1	4.5	0.09
17		0.74	356	160	7.5	9.5	270	70	0.01	0.01			1.44	64	2.15	4.1	4.4	0.11
18		0.80	356	160	7.5	9.5	272	72	0.01	0.01			1.46	64	2.04	3.9	4.3	0.09
19		0.74	356	164	7.5	9.5	270	72	<.01	0.01			1.44	64	2.30	3.8	4.2	0.09
20		0.73	350	162	7.5	9.4	264	74	0.01	0.01			1.47	64	1.83	4.1	4.4	0.10
21		0.72	346	160	7.5	9.4	256	68	<.01	0.01			1.42	65	2.17	4.0	4.3	0.09
22		0.68	344	150	7.5	9.5	268	76	0.01	<.01			1.43	65	2.24	3.6	4.0	0.08
23		0.79	348	156	7.5	9.4	264	70	0.01	0.01			1.43	65	2.18	3.5	4.0	0.07
24		0.76	346	160	7.5	9.5	268	74	0.01	0.01			1.42	65	2.17	3.4	3.8	0.08
25		0.75	348	154	7.5	9.4	264	72	0.01	0.01			1.45	65	2.23	3.4	3.6	0.08
26		0.73	346	154	7.5	9.4	270	74	0.02	<.01			1.47	66	2.23	3.5	3.5	0.09
27		0.73	350	160	7.6	9.4	268	72	<.01	0.01			1.49	66	2.14	3.5	3.3	0.08
28		0.72	350	160	7.5	9.4	268	72	0.01	0.01			1.41	66	2.29	3.5	3.7	0.08
29		0.67	348	152	7.5	9.5	274	76	<.01	0.01			1.42	66	2.36	3.5	3.6	0.07
30		0.72	342	160	7.5	9.5	266	78	0.01	0.01			1.40	66	2.08	3.6	3.1	0.08
AVG		0.73	353	158	7.5	9.4	271	74	0.02	0.01			1.44	64	2.16	4.5	4.7	0.11
MAX		0.89	378	166	7.6	9.6	284	84	0.15	0.01	0.44	0.01	1.49	66	2.36	5.9	6.3	0.38
MIN		0.60	342	150	7.4	9.3	256	68	0.01	0.01	0.44	0.01	1.39	63	1.83	3.4	3.1	0.07

IOWA DEPARTMENT OF NATURAL RESOURCES NPDS REPORTING SYSTEM - DISCHARGE MONITORING REPORT

FACILITY INFORMATION

This form is valid 12/1/2024 to 11/30/2029

	1111S 101111 IS Valid 12/1/2024 to 11/30/2029
Facility Name:	BOONE CITY OF STP
Permit #:	0819001
Month/Year:	9 2025
Outfall #(s):	001 - DISCHARGE FROM AN ACTIVATED SLUDGE WASTEWATER TREATMENT FACILITY.
Operator Name:	John Roberts
Certification #:	10924
Phone #:	7122590805
Lab Cert. #:	156
Comments:	
	*Include Comments longer than 1000 characters in email
Signature:	
· ·	
	John Roberts
	I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for known violations.

Monthly Water & Wastewater Operations Report

Permit # 0819001
Facility Name: BOONE CITY OF STP

Monthly Operation Report IOWA DEPARTMENT OF NATURAL RESOURCES NPDS - Operation Permit System INFLUENT Data

Outfall #: 001 Month/Year: 9-2025

Mon. Point							RAW WASTE						
Parameter	FLOW	ВО	D5	TS	SS	T01	Γ-Ν	TI	KN	PH	OS .	TEMP	PH
Units	MGD	M G/L	LBS/DAY	MG/L	LBS/DAY	M G/L	LBS/DAY	M G/L	LBS/DAY	M G/L	LBS/DAY	FAHRENHEIT	STD UNITS
Frequency	7/WEEK OR DAILY	2 TIMES PER WEEK	2 TIMES PER WEEK	2 TIMES PER WEEK	2 TIMES PER WEEK	1 TIME PER WEEK	1 TIME PER WEEK	1 EVERY MONTH	1 EVERY MONTH	1 TIME PER WEEK	1 TIME PER WEEK	2 TIMES PER WEEK	2 TIMES PER WEEK
Start Date													
End Date	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration
No Discharge													
LOQ													
Day: 1	2.08			165	2862.288							69	
2	1.968					21.34	350.2559808	21	344.67552	4.4	72.217728	69	7.4
3	2.042			165	2809.9962							67	7.4
4	1.864	163	2533.95888									65	7.6
5	1.76	194	2847.6096									65	7.6
6	1.727												
7	1.768												
8	1.689			273	3845.54898							66	7.4
9	1.634					28.3	385.659948	28	381.57168	5.7	77.677092	66	7.5
10	1.604	144	1926.33984	300	4013.208							69	7.5
11	1.602	213	2845.82484									69	7.5
12	1.585												7.4
13	1.56												
14	1.573												
15				262	3266.6946							69	
16	1.502					29.25	366.40539	29	363.27372	5.1	63.886068	70	7.5
17 18	1.48 1.466	164 171	2024.2848 2090.72124	207	2555.0424							68 68	7.2 7.5
	1.391	171	2090.72124									68	7.5
19 20	1.313											08	1.3
20	1.481												
22												72	7.3
22	1.305			251	2731.8087	32.03	348.604911	32	348.2784	4.5	48.97665	68	7.3
23	1.261	170	1787.8458	225	2366.2665	32.03	340.004911	32	340.2704	4.5	40.97000	68	7.3
25	1.316	170	1707.0400	223	2300.2003							68	7.4
26	1.256	207	2168.33328									70	7.4
27	1.237	207	2100.00020									70	7.4
28	1.301												
29				345	3599.5023							70	7.4
30	1.185			343	3033.3023							68	7.4
31	100												7.4
Total	46.117	1426	18224.91828	2193	28050.35568	110.92	1450.92623	110	1437.79932	19.7	262.757538	1432	163.2
Monthly Avg.	1.537233333	178.25	2278.114785	243.6666667	3116.706187	27.73	362.7315575	27.5		4.925	65.6893845	68.19047619	7.418181818
Daily Max.	2.08	213	2847.6096	345	4013.208	32.03	385.659948	32		5.7	77.677092	72	7.6
Daily Min.	1.185	144	1787.8458	165	2366.2665	21.34	348.604911	21	344.67552	4.4	48.97665	65	7.2
Max. 7/Avg.	1.887	188.5	2690.78424	286.5	3929.37849	32.03	385.659948	32		5.7	77.677092	69.2	7.5

	ONE CITY OF STP				onthly Operation Rep RTMENT OF NATURAL																					
				NPDS	- Operation Permit S EFFLUENT Data	ystem																				
Outfall #: 001	1						-																			
Month/Year: 9-2	025																									
Mon. Point													FIN	AL EFFLUENT												
Parameter	CBOD	5	TS	SS	NH	13-N	CHL	ORIDE	CN	T)	NC	3-N	TO'	T-N	PHE	NOLS	P	HOS	TEMP		В	TOX CER	TOX PIM	DO	PH	E COLI
Units	MG/L	LBS/DAY	MG/L	LBS/DAY	M G/L	LBS/DAY	MG/L	LBS/DAY	MG/L	LBS/DAY	MG/L	LBS/DAY	MG/L	LBS/DAY	MG/L	LBS/DAY	MG/L	LBS/DAY	FAHRENHET	MG/L	LBS/DAY	NO TOXICITY	NO TOXICITY	MG/L	STD UNITS	#/100 M L
Frequency 2	TIMES PER WEEK 2	2 TIMES PER WEEK	2 TIMES PER WEEK	1 EVERY MONTH	1 EVERY MONTH	1 TIME PER WEEK	1 TIME PER WEEK	1 EVERY MONTH	1 EVERY MONTH	1 TIME PER WEEK	1 TIME PER WEBK	1 EVERY MONTH	1 EVERY MONTH	1 TIME PER WEEK	1 TIME PER WEEK	2 TIMES PER WEEK	1 TIME PER WEEK	1 TIME PER WEEK	1 EVERY 12 MONTHS	1 EVERY 12 MONTHS	2 TIMES PER WEEK		GEO. MEAN 1/3 MONTHS			
Start Date																										
	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration	Permit Duration				
No Discharge																						06 - NOT REQ / MP	06 - NOT REQ / MP			06 - NOT REQ / MP
LOQ																										
Day: 1	183		1	17.3472															70					6.6	7	9
2	188				0.1	1 641312	2		0.0035	0.05744592			16.71	274 2632353			1.	8 29 543616	70	0.001	0.01641312			-	7	8 4
3	100		3	51.09084	0.1	1.703028			0.0000	2.007 44032			10.71	2.4.2002003			·	25.040010	70	0.001	2.010-1012			6.6	7.	8
4	3	46 63728			0.1	1 554576													66						7	6 6
5	3	44 0352			0.1	1.46784	4												67					6.9	7	7
6	-	44.0002			0.1	1.40704													- 0,					0		
7	100																									
			9	112,69008															66					7.5	7	9
-	100			112.03000	0.1	1.362756	6 150	2044,134	0.0035	0.04769646	14	190,78584	13.67	186.2887452	0.0224	0.305257344	2	2 29.980632	66	0.001	0.01362756			61	7.	7 6
10	3	40.13208	3	40.13208	0.1	1.337736		2044.104	0.0000	0.04700040		130.10004	10.01	1002001402	0.0224	0.000201044	-	20.000002	60	0.001	0.01002700			6.5	7	8
11	3	40.08204			0.1	1.336068													70					7.	7	7 6
12	-	40.00204			0.1	1,32189													70					6.1	7.	7
12					0.1	1.02.100														1				0		
14																										
15			1	37.4049															70					6.0	7	6
16	- 68				0.1	1 252668	9		0.005	0.0626334			10.85	135 914479			2	9 36 327372	75	0.001	0.01252668			7.	7	8
17	2	37 0296	2	24 6864	0.1	1 23432			0.000	0.0020004			10.00	100.014470	1		-	5 55.527572	66	0.001	0.012.02000			61	7	2
18	3	36,67932		24.0004	0.1	1.222644													70					7.3	7	7
10					0.1	1 160094													70					7.	7	7
20							1																			
21	-																									
22							1								1		i e		70	i				7 '	7	7
23			2	21,7674	0.1	1.08837	7		0.0035	0.03809295	9.3	101.21841	10.49	114,170013			3	2 34.82784	70	0.001	0.0108837			7:	7	7
24	2	31.55022	1	31,55022	0.1	1.051674											-		70	-				7.3	7	7
25	188				0.1	1.097544													70					7.0	7	7
26	3	31.42512			0.1	1.047504													70						7	6
27						47004	1								i					1					· ·	
28										1111111111111111111111111111														—	1	1
29			3	31,30002	·		1								i e				70	i e				8.1	7.	9
30					0.1	0.98829	9								l		1		66					8.4	d '	R
31						0.3002													0.					0		
Total	24	307,57086	28	367.96914	1.7	21.868314	150	2044.134	0.0155	0.20586873	22.2	292.00425	51.72	710.6364714	0.0224	0.305257344	10	1 130,67946	1620	0.004	0.05345106			142 6	160	9 22
Monthly Avg.	3	38 4463575	3 111111111	40 88546	0.1	1 286371412	2 150	2044.134	0.0135	0.051467183	11.65		12.93		0.0224	0.305257344	2.52		69 F	0.004	0.03343106			7.13	7 71818181	8 4.4462049
Daily Max.	3	46,63728		112.69008	0.1	1,703028	9 150	2044.134	0.005	0.0626334	14	190,78584	16.71		0.0224	0.305257344		2 36.327372	75	0.001				8.	7.71010101	9 5
Daily Min.	3	31.42512	1	17.3472	0.1	0.98829	9 150	2044.134	0.005	0.0020334	93	101.21841	10.49		0.0224				67	0.001				6.5	7	2
Max. 7/Avg.	3	45 33624		76 41108	0.1	1 501680	0 150	2044.134	0.0035	0.03809293	9.3	190 78584	16.71		0.0224	0.305257344	1.		7/	0.001				7.2	7.7	0 6



1406 Central Avenue Fort Dodge, Iowa 50501 515-269-2338

www.USWUtilityGroup.com

UPGRADE	PROGRAM	August 2025				
DATE	ADDRESS	ORIG INSTALL	Note	Low	Med	High
8/5/2025	608 Carroll	New Service				
8/11/2025	1622 Tama	2/1/2000				
8/11/2025	532 Linden In	2/1/1999				
8/12/2025	214 W Mamie	5/20/2004				
8/12/2025	1328 Nebraska	12/16/2013				
8/13/2025	734 High St	New Service				
8/13/2025	527 Lniden	1/28/1999				
8/13/2025	1722 Nebraska	12/30/2001				
8/13/2025	1825 Linn	2/20/2000				
8/13/2025	1912 SE Linn	7/3/2002				
8/14/2025	2011 Linn	7/20/2006				
8/14/2025	2026 Linn	7/24/2000				
8/14/2025	716 w 8th	pre 99				
8/14/2025	1423 Nebraska	11/1/1999				
8/14/2025	711 Wood	10/13/2005				
8/14/2025	223 Webster					
8/15/2025	611 Linn	3/18/2005				
8/18/2025	302 Sunrise H	5/30/2000				
8/18/2025	302 Sunrise L	5/30/2000				
8/18/2025	303 Morningside	4/15/2005				
8/18/2025	1622 Benton	3/27/2008				
8/21/2025	1416 S Linn	12/23/2003				
8/22/2025	1409 14th					
8/22/2025	315 Sunrise	10/27/2005				
8/22/2025	703 14th	10/06/99				
8/25/2025	1708 14th	pre 99				
	1541 14th	pre 99				
8/25/2025	1020 Ida PI	New Service				
8/26/2025	1115 College	New Service				
8/27/2025	1627 14th	pre 99				
8/28/2025	901 W Mamie	New Service				
8/28/2025	1203 Parkway Dr	New Service				
8/28/2025	726 Marion	7/28/2004				
8/28/2025	1727 14th	1/23/2008				
8/28/2025	1616 14th	pre 99				
8/29/2025	1704 14th	3/3/2005				
8/29/2025	1529 14th	1/16/2004				

UPGRADE	PROGRAM	September 2025				
DATE	ADDRESS	ORIG INSTALL	Note	Low	Med	High
9/8/2025	1120 Coal Rd	Warranty				
9/11/2025	1928 Crawford	6/9/1999				
9/11/2025	368 S Marion	12/14/2006				
9/11/2025	1228 Linn	7/19/2000				
9/12/2025	1105 3rd	9/25/2014				
9/12/2025	1016 14th	10/24/2007				
9/12/2025	1531 14th	3/7/2005				
9/12/2025	1617 14th	3/3/2005				
9/12/2025	903 Crawford	3/28/2005				
9/12/2025	1027 Crawford	7/31/2000				
9/15/2025	2004 Crawford	11/16/1999				
9/15/2025	1710 Crawford	8/9/2000				
9/15/2025	1013 12th	2/25/2004				
9/15/2025	1519 14th	11/18/1999				
	501 Webster	4/22/2004				
9/16/2025	813 W Mamie	9/16/2025				
9/16/2025	1221 Crawford	Pre 1999				
9/16/2025	224 S Marion	05/22/00				
9/17/2025	303 S Main	8/11/2014				
	1227 Crawford	9/18/2003				
9/17/2025		Reinstall				
	2116 Crawford	9/17/1999				
	1211 8th St	New Service				
	1720 Crawford	1/14/2002				
	128 S Montana	6/19/2000				
9/19/2025	816 14th	11/1/1999				
9/19/2025	822 Carroll	11/28/2006				
	1418 Carroll	9/28/2007				
	1910 Crawford	5/10/2000				
	316 S Montana	9/9/1999				
	116 Carroll	3/21/2015				
	1615 Carroll	7/31/2000				
	220 S Main	6/21/2007				
	1403 Crawford	10/5/1999				
	102 Mc Pherson	New Service				
	1510 Carroll	8/7/2000				
	208 S Montana	6/9/2000				
	210 Carroll	3/15/2005				
	230 Story	7/19/1999				
	1922 Carroll	8/14/2000				
	303 W 2nd	6/6/2000				
	2419 Industrial Park Rd	11/25/2013				
	117 W 9th	New Service				
	134 Underhill	12/1/2008				
	1127 Carroll	10/4/1999				
	1527 Carroll	7/25/2000				
	800 Snedden Dr.	6/28/2013				

Curb Box Repair Update for 9/15/2025 – as of 9/9/2025

\$4,501.01 was collected during shut offs. 25 accounts qualified to be on the list.

178 stop boxes need repaired, 76 of which have lead service lines.

11 delinquent bills totaling \$3,550.03 certified on August 28th and if left unpaid, 11 delinquent water bills totaling \$4,803.42 are scheduled to certify on October 6th.

Lesli Vote Utility Billing Supervisor

Curb Box Repair Update for 10/20/2025 – as of 10/10/2025

\$5,961.67 was collected during shut offs. 24 accounts qualified to be on the list.

179 stop boxes need repaired, 75 of which have lead service lines.

5 delinquent bills totaling \$1,942.67 certified on October 10th and if left unpaid, 16 delinquent water bills totaling \$5,241.64 are scheduled to certify on October 28th.

Lesli Vote Utility Billing Supervisor